


Schedule of Accreditation

issued by

United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

 0790 Accredited to ISO/IEC 17025:2005	Phoenix Calibration & Services Ltd	
	Issue No: 016 Issue date: 26 September 2016	
	Unit 8 The Wallows Industrial Estate Fens Pool Avenue Brierley Hill West Midlands DY5 1QA	Contact: Vicki Wilkes Tel: +44 (0)1384 480 545 Fax: +44 (0)1384 480 602 E-Mail: sales@phoenixcalibration.co.uk Website: www.phoenixcalibration.co.uk
Calibration performed by the Organisations at the locations specified below		

Locations covered by the organisation and their relevant activities

Site activities performed away from the locations listed above:

Location details	Activity	Location code
Customers' sites or premises The customer's sites or premises must be suitable for the nature of the particular calibrations undertaken and will be subject of contract review arrangements between the laboratory and the customer	Force	S



0790

Accredited to
ISO/IEC 17025:2005

Schedule of Accreditation
issued by
United Kingdom Accreditation Service
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

Phoenix Calibration & Services Ltd
Issue No: 016 Issue date: 26 September 2016

Calibration performed by the Organisation at the locations specified

DETAIL OF ACCREDITATION

Measured Quantity Instrument or Gauge	Range	Calibration and Measurement Capability (CMC) Expressed as an Expanded Uncertainty ($k = 2$)	Remarks	Location Code
FORCE UNIVERSAL MATERIALS TESTING MACHINES				S
Verification and calibration of the force measuring system by force proving instruments in tension	0.1 kN to 500 kN for Class 0.5, 1, 2 and 3 machines to BS EN ISO 7500-1:2004	0.24 %		
	0.05 kN to 2 MN for Class 1, 2 and 3 machines to BS EN ISO 7500-1:2004	0.32 %		
Verification and calibration of the force measuring system by force proving instruments in tension	From 5.36 kN up to 2 000 kN to ASTM E4-15	0.32 %		
Verification and calibration of the force measuring system by force proving instruments in compression	0.1 kN to 500 kN for Class 0.5, 1, 2 and 3 machines to BS EN ISO 7500-1:2004	0.24 %		
	0.05 kN to 2 MN for Class 1, 2 and 3 machines to BS EN ISO 7500-1:2004	0.32 %		
Verification and calibration of the force measuring system by force proving instruments in compression	From 8.63 kN up to 2 000 kN to ASTM E4-15	0.32 %		
Verification and calibration of the force measuring system by calibrated masses in tension	0.05 N to 270 N for Class 0.5, 1, 2 and 3 machines to BS EN ISO 7500-1:2004	0.10 %		
Verification and calibration of the force measuring system by calibrated masses in compression	0.05 N to 270 N for Class 0.5, 1, 2 and 3 machines to BS EN ISO 7500-1:2004	0.10 %		
CREEP TESTING MACHINES				S
Verification of the applied load using force proving instruments	0.1 kN to 500 kN for Class 0.5, 1.0 and 2.0 machines to BS EN ISO 7500-2:12006	0.24 %		
	0.05 kN to 500 kN for Class 1, 2 and 3 machines to BS EN ISO 7500-2:12006	0.32 %		



0790

Accredited to
ISO/IEC 17025:2005

Schedule of Accreditation
issued by
United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

Phoenix Calibration & Services Ltd

Issue No: 016 Issue date: 26 September 2016

Calibration performed by the Organisation at the locations specified

Measured Quantity Instrument or Gauge	Range	Calibration and Measurement Capability (CMC) Expressed as an Expanded Uncertainty ($k = 2$)	Remarks	Location Code
CREEP TESTING MACHINES (cont'd) Verification of the applied load using masses	0.05 N to 270 N for Class 0.5, 1.0 and 2.0 machines to BS EN ISO 7500-2:2006	0.10 %		
LENGTH Extensometers Cross head and actuator displacement	As BS EN ISO 9513:2012 for the following classes and gauge lengths: Class 0.2 from 25mm Class 0.5 from 10 mm Class 1 from 5 mm Class 2 from 5 mm Displacements 0.02 mm to 5 mm As ASTM:E83-10 for the following classes and gauge lengths: B-1 from 20 mm B-2 from 10mm C from 5 mm Displacements 0.02 mm to 5 mm 0.02 mm to 50 mm 50 mm to 100 mm	3.0 μm) 3.0 μm 0.054 mm 0.064 mm		S
END				