

# Schedule of Accreditation

issued by

## United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

 <b>0262</b> Accredited to <b>ISO/IEC 17025:2017</b>	<b>Testing Calibration Services Limited</b>  <b>Issue No: 038   Issue date: 02 January 2025</b>	
	<b>Unit 5</b> Lincoln Business Park Lincoln Close Rochdale Lancashire OL11 1NR	<b>Contact: Mr D Clayton</b> <b>Tel: +44 (0)1706 359821</b> <b>Fax: +44 (0)1706 712272</b> <b>E-Mail: info@tcslab.co.uk</b> <b>Website: www.tcslab.co.uk</b>
Calibration performed by the Organisations at the locations specified below		


### Locations covered by the organisation and their relevant activities

#### Laboratory locations:

Location details	Activity	Location code
<b>Address</b> Unit 5 Lincoln Business Park Lincoln Close Rochdale Lancs OL11 1NR  <b>Contact</b> Mr D Clayton	Force	P

#### Site activities performed away from the locations listed above:

Location details	Activity	Location code
Any customers' sites or premises must be suitable for the nature of the particular calibrations undertaken and will be the subject of contract review arrangements between laboratory and the customer.  <b>Contact</b> Mr D Clayton	Force	S




**Testing Calibration Services Limited**  
**Issue No: 038      Issue date: 02 January 2025**

**Calibration performed by the Organisation at the locations specified**

### Calibration and Measurement Capability (CMC)

Measured Quantity Instrument or Gauge	Range	Expanded Measurement Uncertainty ( $k = 2$ )	Remarks	Location Code
FORCE				S
UNIVERSAL MATERIALS TESTING MACHINES				
Verification and calibration of the force measuring system by force proving instruments in Tension	0.05 kN to 600 kN for Class 0.5, 1, 2 and 3 machines to BS EN ISO7500- 1:2018 and ASTM E4-20	0.22 %		
Verification and calibration of the force measuring system by force proving instruments in Compression	0.05 kN to 600 kN for Class 0.5, 1, 2 and 3 machines to BS EN ISO7500-1:2018 and ASTM E4-21	0.22 %		
Verification and calibration of the force measuring system by calibrated masses in Tension	0.001 N to 500 N for Class 0.5, 1, 2 and 3 machines to BS EN ISO7500-1:2018 and ASTM E4-21	0.10 %		
Verification and calibration of the force measuring system by calibrated masses in Compression	0.001 N to 500 N for Class 0.5, 1, 2 and 3 machines to BS EN ISO7500-1:2018 and ASTM E4-21	0.10 %		P
FORCE MEASURING DEVICES				
Calibration of force measuring devices (e.g. strain gauged load cells, push pull gauges, and load measuring rings) but excluding proving devices by force proving instruments and masses in tension	From 0.001 N up to 2 kN From 0.05 kN up to 100 kN	0.10 % 0.41 %		
Calibration of force measuring devices (e.g. strain gauged load cells, push pull gauges, and load measuring rings) but excluding proving devices by force proving instruments and masses in compression	From 0.001 N up to 2 kN From 0.05 kN up to 180 kN	0.10% 0.41%		



**Testing Calibration Services Limited**  
**Issue No: 038      Issue date: 02 January 2025**

**Calibration performed by the Organisation at the locations specified**

END



0262  
Accredited to  
ISO/IEC 17025:2017

**Schedule of Accreditation**  
issued by  
**United Kingdom Accreditation Service**  
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

**Testing Calibration Services Limited**  
**Issue No:** 038    **Issue date:** 02 January 2025

Calibration performed by the Organisation at the locations specified

**Appendix - Calibration and Measurement Capabilities**

**Introduction**

The definitive statement of the accreditation status of a calibration laboratory is the Accreditation Certificate and the associated Schedule of Accreditation. This Schedule of Accreditation is a critical document, as it defines the measurement capabilities, ranges and boundaries of the calibration activities for which the organisation holds accreditation.

**Calibration and Measurement Capabilities (CMCs)**

The capabilities provided by accredited calibration laboratories are described by the Calibration and Measurement Capability (CMC), which expresses the lowest measurement uncertainty that can be achieved during a calibration. If a particular device under calibration itself contributes significantly to the uncertainty (for example, if it has limited resolution or exhibits significant non-repeatability) then the uncertainty quoted on a calibration certificate will be increased to account for such factors.

The CMC is normally used to describe the uncertainty that appears in an accredited calibration laboratory's schedule of accreditation and is the uncertainty for which the laboratory has been accredited using the procedure that was the subject of assessment. The measurement uncertainty is calculated according to the procedures given in the GUM and is normally stated as an expanded uncertainty at a coverage probability of 95 %, which usually requires the use of a coverage factor of  $k = 2$ . An accredited laboratory is not permitted to quote an uncertainty that is smaller than the published measurement uncertainty in certificates issued under its accreditation.

**Expression of CMCs - symbols and units**

It should be noted that the percentage symbol (%) represents the number 0.01. In cases where the measurement uncertainty is stated as a percentage, this is to be interpreted as meaning percentage of the measurand. Thus, for example, a measurement uncertainty of 1.5 % means  $1.5 \times 0.01 \times q$ , where  $q$  is the quantity value.

The notation  $Q[a, b]$  stands for the root-sum-square of the terms between brackets:  $Q[a, b] = [a^2 + b^2]^{1/2}$