


Schedule of Accreditation

issued by

United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

 <p>0606</p> <p>Accredited to ISO/IEC 17025:2017</p>	<h3>Guy's and St Thomas' Hospital Trust</h3> <p>Issue No: 022 Issue date: 10 November 2025</p>	
	<p>Non-Ionising Radiation Medical Physics</p> <p>South Wing, Block C 3rd Mezzanine Floor Guy's and St Thomas' NHS Foundation Trust London SE1 7EH</p>	<p>Contact: Grace Aneju Tel: +44 (0)20 7188 0733 E-Mail: uv_ukaslab@gstt.nhs.uk Website: http://www.guysandstthomas.nhs.uk/our-services/medical-physics/medical-physics.aspx</p>
<p>Calibration performed at the above address only</p>		

Calibration and Measurement Capability (CMC)

Measured Quantity Instrument or Gauge	Range	Expanded Measurement Uncertainty ($k = 2$)	Remarks
RADIOMETRY			
Spectral responsivity of UV detectors at power levels between: 0.1 mWcm ⁻² and 2.0 mWcm ⁻²	Specified wavelength: 365 nm	10 %	
	Other specific wavelengths in the range 250 nm to 600 nm	10 %	
Responsivity of UV detectors at power levels between: 0.1 mWcm ⁻² and 2.0 mWcm ⁻²	UVA and UVB	14 %	Comparison calibration for Waldmann and IL1400 UV radiometers using UVA and TL01 phototherapy lamps
END			



0606
Accredited to
ISO/IEC 17025:2017

Schedule of Accreditation (DRAFT)
issued by
United Kingdom Accreditation Service
21 - 47 High Street, Feltham, Middlesex, TW13 4UN, UK

Guy's and St Thomas' Hospital Trust
Issue No: 022 Issue date: 10 November 2025

Calibration performed at main address only

Appendix - Calibration and Measurement Capabilities

Introduction

The definitive statement of the accreditation status of a calibration laboratory is the Accreditation Certificate and the associated Schedule of Accreditation. This Schedule of Accreditation is a critical document, as it defines the measurement capabilities, ranges and boundaries of the calibration activities for which the organisation holds accreditation.

Calibration and Measurement Capabilities (CMCs)

The capabilities provided by accredited calibration laboratories are described by the Calibration and Measurement Capability (CMC), which expresses the lowest measurement uncertainty that can be achieved during a calibration. If a particular device under calibration itself contributes significantly to the uncertainty (for example, if it has limited resolution or exhibits significant non-repeatability) then the uncertainty quoted on a calibration certificate will be increased to account for such factors.

The CMC is normally used to describe the uncertainty that appears in an accredited calibration laboratory's schedule of accreditation and is the uncertainty for which the laboratory has been accredited using the procedure that was the subject of assessment. The measurement uncertainty is calculated according to the procedures given in the GUM and is normally stated as an expanded uncertainty at a coverage probability of 95 %, which usually requires the use of a coverage factor of $k = 2$. An accredited laboratory is not permitted to quote an uncertainty that is smaller than the published measurement uncertainty in certificates issued under its accreditation.

Expression of CMCs - symbols and units

It should be noted that the percentage symbol (%) represents the number 0.01. In cases where the measurement uncertainty is stated as a percentage, this is to be interpreted as meaning percentage of the measurand. Thus, for example, a measurement uncertainty of 1.5 % means $1.5 \times 0.01 \times q$, where q is the quantity value.

The notation $Q[a, b]$ stands for the root-sum-square of the terms between brackets: $Q[a, b] = [a^2 + b^2]^{1/2}$