Schedule of Accreditation

issued by

United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

UKAS TESTING **1204** **Accredited to ISO/IEC 17025:2017**	**3C Test Ltd** **Issue No:** 072 **Issue date:** 10 July 2026	
	Silverstone Technology Park **Silverstone Circuit** **Silverstone** **Northamptonshire** **NN12 8GX**	**Contact: Mr Shaun Butler** **Tel: +44 (0)1327 857500** **E-Mail: shaun.butler@applus.com** **Website: www.3ctest.co.uk**
Testing performed by the Organisation at the locations specified below		

Locations covered by the organisation and their relevant activities

Laboratory locations:

Location details		Activity	Location code
Silverstone Technology Park Silverstone Circuit Silverstone Northamptonshire NN12 8GX	**Local contact** Mr Shaun Butler	EMC testing	A
Unit 1505 Silverstone Park Silverstone Northamptonshire NN12 8FU	**Local contact** Mr Shaun Butler	EMC & Environmental testing	B

Flexible Scope

The Flexible Scope applies to the laboratory's accreditation to ISO/IEC17025:2017 for testing activities in accordance with the standards listed in sections 1, 2, 3 and 5 & internal procedure: 3CSP_008 Iss3.0

The scope may also include tests on the same or similar product types against standards, or customer-specified methods that are not specifically listed in this Schedule, providing that:
(1) The method or standard does not introduce new principles of measurement.
(2) The method or standard does not require measurements to be made outside the parametric boundaries defined in this Schedule.

Information about flexible scopes of accreditation is available in UKAS document GEN4.

Note:

The EN specifications listed within this schedule of accreditation have been adopted nationally as BS EN publications. Please note that they are technically equivalent to the internationally released publications (for example DIN EN, IEC, UNE-EN, I.S EN etc).

DETAIL OF ACCREDITATION

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used	Location Code
Aerospace Equipment Compressors	**1 CIVIL EMC TESTS**		
Computers and peripherals Construction Plant and Equipment Domestic Appliances: Electrical Electrical/electronic Components Electrical/electronic Connectors Electrical/electronic Products Electro-Mechanical Devices Electronic Products, Digital Enclosures for Electrical Equipment Fans Flowmeters Gas Appliances Generators: Electrical Generators: Power Generators: Welding IT Equipment Instruments: Indicating/Recording Lamps: Electrical Lawnmowers Lifts: Electrical Marine Equipment Measuring Equipment Military Equipment Motor Vehicle Accessories and Components Motor Vehicles Motors: Electrical Printed Circuit Boards Radio and TV Equipment Safety Appliances and Equipment Switchboards: Electrical Telecommunication Equipment Tools: Hand (Electrical) Video Equipment	1.1 Conducted Emissions 9 kHz to 300 MHz AC mains: Single phase up to 32A Voltage up to 240 V Three phase up to 32A Voltage up to 415 V Continuous and Discontinuous DC voltage, up to 60V/100A	CISPR 16-2-1:2005 (Ed 1.1) EN 55011:1991 EN 55011:1998+A1:1999+A2:2002 EN 55011:2007+A2:2007 EN 55011:2009+A1:2010 EN 55011: 2016 +A1:2017 +A2 :2021 CISPR 11:2009+A1:2010 EN 55014-1:1993+A1:1997 EN 55014-1:1997 EN 55014-1:2006 EN 55014-1:2006+A1:2009 EN 55014-1:2006+A2:2011 EN 55014-1: 2017 +A1:2021 EN 55022:1995+A1:1995+A2:1997 EN 55022:1998+A1:2000+A2:2003 CISPR 22:1997+A1:2000+A2:2002 EN 55022:2006+A1:2007 CISPR 22:2005 EN 55022:2010 ANSI C63.4:1992 ANSI C63.4:2003 ANSI C63.4:2009 ANSI C63.4:2014 EN 55032:2015 EN 55032:2015	A, B
	1.2 Radiated Emissions: 150 kHz to 18 GHz	ANSI C63.4:2009 FCC CFR 47 Part 15B ICES 003:2004 Germanischer Lloyd GL 2001, VI, Part 7, Chapter 3, Section 3 Part B21 CISPR 16-2-3:2006 CISPR 16-2-3: 2010 CISPR 16-2-3: 2016	A, B

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used	Location Code
As listed on Page 2	**1 CIVIL EMC TESTS** (cont'd)		
	1.2 Radiated Emissions: 150 kHz to 18 GHz AC mains: as in 1.1 (cont'd)	EN 55011:1991 EN 55011:1998+A1:1999+A2:2002 EN 55011:2007+A2:2007 EN 55011:2009+A1 2010 EN 55011: 2016 +A1:2017 +A2 :2021 CISPR 11:2009+A1 2010 EN 55022:2006+A1:2007 CISPR 22:2005 EN 55022:2010 CISPR 22:2009 ANSI C63.4:2003 ANSI C63.4:2009 FCC/OST MP-5:1986 FCC CFR 47 Part 15B Including boresight measurement FCC CFR 47 Part 18 ICES 003:2004 Germanischer Lloyd GL 2001, VI, Part 7, Chapter 3, Section 3, Part B22 EN 55032:2015 EN 55012:2007 + A1:2009	A, B
	1.3 Harmonic Emissions up to 75 A	EN 61000-3-2:2006 EN 61000-3-2:2006+A2:2009 EN 61000-3-2:2014 EN 61000-3-2: 2019 EN 61000-3-12: 2011	A, B

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used	Location Code
As listed on Page 2	**1 CIVIL EMC TESTS** (cont'd) 1.4 Flicker Measurement **up to 75 A**	EN 61000-3-3:1995+A1:2001 **+A2:2006** EN 61000-3-3:2008 EN 61000-3-3:2013 EN 61000-3-3: 2013 + A1: 2019 EN 61000-3-11 2001 EN 61000-3-11: 2019	A, B
	1.5 Fast Transient/Burst Immunity 0.5 to 4.0 kV 5/50 nsec, 5 kHz repetition AC mains: as in 1.1	EN 61000-4-4:1995+A1:2001 +A2:2002 EN 61000-4-4:2004 EN 61000-4-4:2004+A1:2010 EN 61000-4-4:2012	A, B
	1.6 Surge Immunity Waveforms 1.2/50 (8/20) μs AC mains: as in 1.1	EN 61000-4-5:1995+A1:2001 EN 61000-4-5:2006 EN 61000-4-5:2014 EN 61000-4-5:2014 + A1: 2017	A, B
	1.7 AC Power Ports Voltage Dips, Interruptions and Fluctuations AC mains: as in 1.1	EN 61000-4-11:1994+A1:2001 EN 61000-4-11:2004 EN 61000-4-11:2004 + A1:2017 EN 61000-4-11:2021	A, B

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used	Location Code
As listed on Page 2	**1 CIVIL EMC TESTS** (cont'd)		
	1.8 Radiated Immunity 80 MHz to 1000 MHz at 20V/m (10 V/m location B) 1 to 2.7 GHz at 10 V/m 2.7 to 6 GHz at 3 V/m (AM modulated for the above ranges) Spot frequencies with pulse modulation as per the requirements of EN 60601-1-2: 2015 +A1:2021 AC mains: as in 1.1	EN 61000-4-3:1996 EN 61000-4-3:2002+A1:2002 EN 61000-4-3:2006 EN 61000-4-3 2006+A1:2008 +A2:2010 EN 61000-4-3:2020	A, B
	1.9 Power Frequency Magnetic Fields (Immunity) Frequency: 50 Hz Field strength: 100 A/m AC mains: as in 1.1	EN 61000-4-8:1994 EN 61000-4-8:2010	A, B
	1.10 Pulse Magnetic Immunity Field strength: 1000 A/m AC mains: as in 1.1	EN 61000-4-9:1994	A, B
	1.11 Conducted Immunity 150 kHz to 230 MHz RF voltage up to 10 Vrms AC Mains: as in 1.1	EN 61000-4-6:1996+A1:2001 EN 61000-4-6:2007 EN 61000-4-6:2009 EN 61000-4-6: 2014	A, B
	1.12 Electrostatic Discharge Immunity Positive and Negative Polarity (ESD) up to 20 kV • Direct and Indirect • Air and Contact Discharge	EN 61000-4-2:1995+A1:1998 +A2:2001 EN 61000-4-2:2009	A, B

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used	Location Code
As listed on Page 2	**1 CIVIL EMC TESTS** (cont'd)		
	1.13 Magnetic Fields Immunity 9 kHz to 26 MHz Up to 65 A/m AC Mains: as in 1.1	EN 61000-4-39:2017 IEC 61000-4-39:2017	A, B
	1.14 Generic Standards These Generic and Product specific tests are included in this Schedule, but limited to those referred basic standards that are explicitly listed in Sections 1.1 to 1.13. Note: International Standards EN, ENV and IEC, listed in this Schedule, that have been adopted nationally as BS EN DD ENV and BS IEC and are technically	EN 61000-6-1:2001 EN 61000-6-1:2007 EN 61000-6-2:2001 EN 61000-6-2:2005 EN 61000-6-2:2019 EN 61000-6-3:2001+A11:2004 EN 61000-6-3:2007 EN 61000-6-3:2007+A1:2011 EN 61000-6-4:2001 EN 61000-6-4:2007 EN 61000-6-4:2007+A1:2011 EN 61000-6-4: 2019 EN 50081-1:1992 EN 50081-2:1994 EN 50082-1:1992 EN 50082-1:1997 EN 50082-2:1994 EN 50121-4:2006 EN 50121-4: 2016 EN 50121-3-2:2006 EN 50121-3-2: 2016 EN 50130-4:1995 +A1:1998+A2:2003 EN 50130-4:2011 EN 50130-4:2011 +A1:2014 EN 50270:2006 EN 50270:2015 EN 50293:2000 EN 60601-1-2:1993 EN 60601-1-2:2001 EN 60601-1-2:2007 EN 60601-1-2:2015 +A1:2021 IEC 60601-1-2:2014 +A1:2020 EN 55014-2:1997+A1:2001 EN 55014-2:1997+A2:2008	A, B

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used	Location Code
As listed on Page 2	**1 CIVIL EMC TESTS** (cont'd) 1.14 Generic Standards (cont'd)	EN 55014-2:1997 +A1:1998+A2:2001+A3:2007 EN 55014-2:2015 EN 55016-1-1: 2019 EN 55016-1-2: 2014 +A1: 2018 EN 55016-2-1: 2015 + A1: 2018 EN 55035: 2017 EN 61326:1997 +A1:1998+A2:2001+A3:2003 EN 61326-1:2006 EN 61326: 2013 EN 61326-1:2021 EN 61326-2-1:2021 EN 61326-2-6:2021 EN 55024:1998+A1:2001+A2:2003 CISPR 24:1997+A1:2001+A2:2002 EN 55024:2010 EN 60945:2002, section 9 & 10 EN 61800-3:2004+A1:2012 excluding Clause 6.2.2, 6.2.3.2, 6.2.3.3,6.2.4.2, 6.2.4.3 & 6.2.5 Note: Up to 16 Amps for EN 61000-3-2 and EN 61000-3-3 and up to 32 Amps per phase other tests (include any exceptions or limitations) EN 50498:2010 ECE Regulation 10.04 Excluding 3 Phase Charge point testing for harmonics and Flicker ECE Regulation 10.05 Excluding 3 phase charge point for harmonics and flicker ECE Regulation 10.06 Excluding 3 phase charge point for harmonics and flicker EN 301 489-1: V1.9.2 : 2011 EN 301 489-3: V1.6.1 : 2013	A, B

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used	Location Code
As listed on Page 2	**2 AUTOMOTIVE**		
	2.1 Conducted Emissions 9 kHz to 300 MHz	CISPR 25:2002 CISPR 25:2008 CISPR 25:2016 ECE Regulation 10.04 Annex 13 & 14 ECE Regulation 10.05 Annex 13, 14, 19 & 20 ECE Regulation 10.06 Annex 13, 14, 19 & 20 EN 61851-21-1: 2017	A, B
	2.2 Radiated Emissions: 150 kHz to 18 GHz Measurement of Magnetic and Electric Field Strength from Electric Vehicles 9kHz to 30MHz Earth Moving & Construction Machinery: Vehicle and Components	CISPR 25:2002 CISPR 25:2008 CISPR 25:2016 EC Directive 72/245/EC EC Directive 95/54/EC, Annex 7 and 8 EC Directive 2004/104/EC, Annex IV, V, VII and VIII EC Directive 2006/28/EC EC Directive 97/24/EC, chapter 8 Annex II and III Annex V and VI SAE J1551-5 Jan 2004 SAE J1551-5 May 2012 EN 61851-21-1: 2017 EC Directive 2009/64/EC ISO 13766:2006 ISO 13766-1: 2018 EN ISO 14982:1998 EN 14982:2009 EN 13309:2000 EN 13309:2010 ECE Regulation 10.04 Annex 4,5, 7 & 8 ECE Regulation 10.05 Annex 4,5, 7 & 8 ECE Regulation 10.06 Annex 4, 5, 7 & 8	A, B

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used	Location Code
As listed on Page 2	**2 AUTOMOTIVE** (cont'd)		
	2.3 Radiated Immunity Absorption Chamber Whole Vehicle and Component 400 MHz - 6 GHz at 200 V/m 6 GHz – 10 GHz at 100V/m 1.2 GHz - 3.4 GHz at 600V/m Earth Moving & Construction Machinery: Vehicle and Components	SAE J1113-21:1998 ISO 11452-2:1995 ISO 11452-2:2004, substitution method ISO 11452-2:2019 EC Directive 72/245/EC EC Directive 2004/104/EC, Annex VI and IX EC Directive 2006/28/EC EC Directive 97/24/EC, chapter 8 Annex IV and Annex VII EC Directive 2009/64/EC ISO 13766:2006 ISO 13766-1: 2018 ISO 13766-2: 2018 EN ISO 14982:1998 EN ISO 14982: 2009 EN13309:2000 EN13309:2010	A, B
	2.4 Radiated Immunity Absorption Chamber Transverse Electromagnetic (TEM) Cell 10 kHz to 300MHz Stripline 10 kHz to 400 MHz Portable Transmitters Magnetic Field 15Hz to 150kHz	SAE J1113-25:1999 SAE J1113-23:1995 ISO 11452-3:2016 ISO 11452-5:2004, 150mm stripline substitution method EC Directive 72/245/EC EC Directive 95/54/EC, Annex 9 EC Directive 2004/104/EC, Annex IX EC Directive 2006/28/EC EC Directive 97/24/EC, chapter 8 ECE Regulation 10.04 Annex 6 & 9 ECE Regulation 10.05 Annex 6 & 9 ECE Regulation 10.06 Annex 6 & 9 ISO 11452-9: 2012 ISO 11452-8: 2007 ISO 11452-8: 2015 EN 61851-21-1: 2017 ISO 11451-2: 2015 ISO 11451-3: 2015	A, B

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used	Location Code
As listed on Page 2	**2 AUTOMOTIVE** (cont'd) 2.5 Radiated Immunity Reverberation Chamber 200 MHz to 1 GHz up to 1300 V/m 1 GHz to 6 GHz up to 700 V/m	ISO 11452-11:2010	B
	2.6 Conducted Immunity 150 kHz to 230 MHz RF Voltage up to 10 Vrms BCI 100 kHz to 400 MHz	ISO 11452-4:2001 ISO 11452-4:2005, subst. method ISO 11452-4:2011 (excluding TWC test method) ISO 11452-4:2020 (excluding TWC test method) EC Directive 72/245/EC EC Directive 95/54/EC, Annex 9 EC Directive 2004/104/EC, Annex IX EC Directive 2006/28/EC EC Directive 97/24/EC, chapter 8 Annex VII ECE Regulation 10.04 Annex 6 & 9 ECE Regulation 10.05 Annex 6 & 9 ECE Regulation 10.06 Annex 6 & 9 EN 61851-21-1: 2017	A, B
	2.7 Electrostatic Discharge Immunity Positive and Negative Polarity (ESD) Up to 20 kV • Direct and Indirect • Air and Contact Discharge	ISO 10605:2001 ISO 10605:2008 ISO 10605: 2008 + corrigendum March 2010 ISO 10605:2008+A1:2014 ISO 13766:2006 ISO 13766-1: 2018 ISO 13766-2: 2018 EN ISO 14982:1998 EN ISO 14982: 2009 EN13309:2000 EN13309:2010	A, B

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used	Location Code
As listed on Page 2	**2 AUTOMOTIVE** (cont'd)		
	2.8 Vehicle and component Transient Testing 12 and 24 v Emissions and Immunity Harmonics & Flicker Burst & Surge	ISO 7637-1:1990, except Pulse 5 ISO 7637-2:1990, except Pulses 1, 2, 5 ISO 7637-2:2004 ISO 7637-2: 2011 ISO 7637-3:1995 ISO 7637-3: 2007 ISO 7637-3:2016 ISO 16750-2: 2006 ISO 16750-2: 2010 ISO 16750-2: 2012 ECE Regulation 10.04 Annexes 10, 11, 12, 15 & 16 ECE Regulation 10.05 Annexes 10, 11, 12, 15, 16, 17,18, 21, & 22 ECE Regulation 10.06 Annexes 10, 11, 12, 15, 16, 17, 18, 21 & 22 EN 61851-21-1: 2017	A, B
	2.9 EMF exposure tests 1 Hz to 400 kHz Frequency Range	RE320 ICNIRP: 1998 Reference Levels, FMC1278 Revision 3, Time Domain Assessment Method to EN62311: 2008	A, B
	2.10 Generic Automotive Standards	ISO 11451-1: 2005 ISO 11451-1: 2015 ISO 7637-1: 2002 ISO 7637-1: 2015	A, B

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used	Location Code
As listed on Page 2	**3 MILITARY EMC TESTS Component and sub system** 3.1 Conducted Emissions 20 Hz to 200 MHz	DEF STAN 59-411 Part 3 Issue 3: 2019 DCE01.B & DCE02.B MIL STD 461G:2015 CE101 & CE102	A, B
	3.2 Radiated Emissions 10 kHz to 18 GHz	DEF STAN 59-411 Part 3 Issue 3: 2019 DRE01.B MIL STD 461G:2015 RE102	A, B
	3.3 Radiated Susceptibility 10 kHz to 1 MHz: 356 V/m 10 MHz to 1 GHz: 200 V/m 1 GHz to 18 GHz: 200 V/m (with 1.2 GHz to 1.4 GHz, 2.7 GHz to 3.1 GHz 600 V/m)	DEF STAN 59-411 Part 3 Issue 3: 2019 DRS02.B MIL STD 461G:2015 RS103	A, B
	3.4 Electrostatic Discharge Up to 25 kV	DEF STAN 59-411 Part 3 Issue 3: 2019 DCS10.B MIL STD 461G:2015 CS118	A, B
	3.5 Conducted Susceptibility 20 Hz to 400 MHz	DEF STAN 59-411 Part 3 Issue 3: 2019 DCS01.B, DCS02.B, DCS03.B MIL STD 461G:2015 CS101, CS114, CS115 & CS116	A, B
	3.6 Magnetic Field Susceptibility 20 Hz to 100 kHz Up to 4800 A/m	DEF STAN 59-411 Part 3 Issue 3: 2019 DRS01.B & DRS03.B MIL STD 461G:2015 RS101	A, B

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used	Location Code
As listed on Page 2	**3 MILITARY EMC TESTS Component and sub system** (cont'd)		
	3.7 Magnetic Field Emissions 20 Hz to 100 kHz	DEF STAN 59-411 Part 3 Issue 3: 2019 DRE02.B MIL STD 461G:2015 RE101	A, B
	3.8 Exported Transients – Power Lines 20 Hz to 150 kHz	DEF STAN 59-411 Part 3 Issue 3: 2019 DCE03.B	A, B
	3.9 Externally Generated Transients	DEF STAN 59-411 Part 3 Issue 3: 2019 DCS05.B & DCS06.B MIL STD 461G:2015 CS116	A, B
UNINTENTIONAL RADIATORS	**4 UK/US MRA Accredited Scope** Conducted Emissions 9 kHz to 30 MHz Radiated Emissions 30 MHz to 18 GHz	ANSI C63.4-2014 FCC Part 15, subpart B	A, B
INDUSTRIAL, SCIENTIFIC AND MEDICAL EQUIPMENT Consumer ISM Equipment	Conducted Emissions 9 kHz to 30 MHz Radiated Emissions 30 MHz to 18 GHz	FCC MP-5 (February 1986), FCC Part 18	A, B

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used	Location Code
As listed on Page 2	**5 ENVIRONMENTAL TESTS** 5.1 CLIMATIC 5.1.1 Low Temperature Steady state and cycling Minimum Temperature -70 ºC Humidity 10 to 95%	BS EN 60068-2-1: 2007 Cold ISO 16750-4:2010 Section 5.1.1 ISO 16750-4:2023 Section 5.1.1 DEF STAN 00-035 Pt 3, Issue 5: 2017 Test CL5 MIL-STD 810H:2019 Method 502.7 Procedure I Storage Procedure II Operation Procedure III Manipulation	B
	5.1.2 High Temperature Steady state and cycling Maximum Temperature 200 ºC Humidity 10 to 95%	BS EN 60068-2-2: 2007 Dry Heat ISO 16750-4:2010 Section 5.1.2 ISO 16750-4:2023 Section 5.1.2 DEF STAN 00-035 Pt 3, Issue 5: 2017 Test CL2 MIL-STD 810H:2019 Method 501.7 Procedure I Storage Procedure II Operation DEF STAN 00-035 Pt 3, Issue 5: 2017 Test CL6 RTCA DO 160G CHG1:2014 Section 6 Humidity MIL-STD 810H:2019 Method 507.6 Procedure I Induced (Storage and Transit) Cycles Procedure I Natural Cycles Procedure II Aggravated Cycle	B

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used	Location Code
As listed on Page 2	**5 ENVIRONMENTAL TESTS** (cont'd) 5.1.3 Thermal Shock Automated transfer Minimum Temperature -60 ºC Maximum Temperature 200 ºC	BS EN 60068-2-14: 2009 BS EN 60068-2-14: 2023 Change of Temperature Na - Prescribed transfer time Nb – Change of temperature with specified rate of change ISO 16750-4:2010 Section 5.3 ISO 16750-4:2023 Section 5.3 UNECE Regulation 100.3 Paragraph 6.3 (Annex 9B) DEF STAN 00-035 Pt 3, Issue 5: 2017 CL14 RTCA DO 160G CHG1:2014 Section 5 Temperature Variation, Category S1 & S2 MIL-STD 810H:2019 Method 503.7 RTCA DO 160G CHG1:2014 Section 5 Temperature Variation, Category A, B & C	B
	5.1.4 Thermal Cycling Minimum Temperature -70 ºC Maximum Temperature 200 ºC	BS EN 60068-2-14: 2009 Nb - Rate of change ISO 16750-4:2010 Section 5.3 ISO 16750-4:2023 Section 5.3 ST/SG/AC.10/11/Rev.7/Amend.1 UN 38.3 section 38.3.4.2 T2 UNECE Regulation 100.3 Paragraph 6.3 (Annex 9B)	B
	5.1.5 High/Low Temperature & Humidity Steady state and cycling Humidity 10 to 95%	BS EN 60068-2-30: 2005 Damp Heat Cyclic BS EN 60068-2-78: 2013 Damp Heat Steady State BS EN 60068-2-38: 2021 Z/AD Composite temp/hum cyclic test ISO 16750-4:2010 Section 5.6, 5.7 ISO 16750-4:2023 Section 5.6 Tests 1 & 3, Section 5.7	B

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used	Location Code
As listed on Page 2	**5 ENVIRONMENTAL TESTS** (cont'd) 5.1.6 Salt Spray Chamber size 0.72 m x 1.60 m x 0.65 m	BS EN 60068-2-11: 2021 Ka Salt Mist BS EN 60068-2-52: 2018 Kb Salt Mist Cyclic ISO 16750-4:2010 Section 5.5 ISO 16750-4:2023 Section 5.5 ISO 9227:2022 DEF STAN 00-035 Pt 3, Issue 5: 2017 Test CN2 RTCA DO 160G CHG1:2014 14 Salt Spray MIL-STD 810G 2019 Method 509.7 Procedure I Corrosion Screening Procedure II Design Corrosion Verification	B
	5.1.7 Low Pressure Temperature range: Ambient temperature Minimum Pressure: 1.0 kPa (10.0 mbar) Maximum chamber size: 1.0 m x 1.0 m x 1.0 m	ST/SG/AC.10/11/Rev.7/Amend.1 UN 38.3 section 38.3.4.1 T1 DEF STAN 00-035 Pt 3, Issue 5: 2017 Test CL11, A1 to A3 only RTCA DO 160G CHG1:2014 4.6.1 Altitude Test MIL-STD 810G 2019 Method 500.6 Procedure I (Storage/Air Transport) Procedure II (Operation/Air Carriage). BS EN 60068-2-13:2021 Test M Low air pressure	B

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used	Location Code
As listed on Page 2	**5 ENVIRONMENTAL TESTS** (cont'd) 5.2 DYNAMIC 5.2.1 Vibration Sine, Random and Mixed Mode Frequency range: 5-3300 Hz Acceleration up to 100g peak Velocity up to 2.0 m/s peak Displacement up to 76.2 mm peak to peak Thrust up to 200 kN Maximum payload: 5250 kg Max temp: +130°C Min temp: -40°C Humidity: 25% to 95% RH	BS EN 60068-2-6: 2008 Fc: Vibration (sinusoidal) BS EN 60068-2-64: 2008 Fh: Vibration, broadband random EN 60068-2-80: 2005 ISO 16750-3: 2012 Section 4.1 ISO 16750-3: 2023 Section 4.1 ST/SG/AC.10/11/Rev.7/Amend.1 UN 38.3 section 38.3.4.3 T3 UNECE Regulation 100.3 Paragraph 6.2 (Annex 9A) DEF STAN 00-035, Part 3, Chapter 2-01, Issue 5:2017, Test M1 General Purpose Vibration Test RTCA/DO-160G CHG 1:2014, Section 8.0 – Vibration MIL-STD-810H w/Change 1:15 April 2014, Method 514.8 – Vibration, Procedure I – General Vibration	B

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used	Location Code
As listed on Page 2	**5 ENVIRONMENTAL TESTS** (cont'd) 5.2.2 Shock Severity: to 200 g peak Velocity up to 3.5 m/s pk Displacement up to 76.2 mm peak to peak Thrust up to 200 kN Maximum payload: 5250 kg	BS EN 60068-2-27:2009 Ea: Shock ISO 16750-3:2012 Section 4.2 ISO 16750-3:2023 Section 4.2 ST/SG/AC.10/11/Rev.7/Amend.1 UN 38.3 section 38.3.4.4 T4 DEF STAN 00-035, Part 3 Issue 5:2017, Test M3 – General Purpose Shock Classical Pulse Test Procedure RTCA/DO-160G 2014 Section 7.0 Operational Shocks and Crash Safety Test Procedure I (Impulse) MIL-STD-810H w/Change 1:15 April 2014, Method 516.8 – Shock	B
	5.2.3 Rough Handling Max drop height: 5m	BS EN 60068-2-31:2009 Ec: Rough handling shocks DEF STAN 00-035 Part 3 Issue 5:2017 Test M4 Drop, Topple and Roll Test DEF STAN 00-035 Part 3 Issue 5: 2017 Test M5 - Vertical Impact Test only	B

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used	Location Code
As listed on Page 2	**5 ENVIRONMENTAL TESTS** (cont'd) 5.2.4 Rolling Stock Frequency range: 5 - 3300 Hz Shock: up to 200g peak Random vibration acceleration up to 70g RMS Velocity up to 3.5m/s peak Displacement up to 76.2 mm peak to peak Thrust up to 200 kN RMS Maximum payload: 5250 kg	 BS EN 61373: 2010 Rolling stock equipment – shock and vibration tests Category 1A, 1B, 2 and 3	 B B
Electrical Equipment for Measurement, Control and Laboratory use.	**6 ELECTRICAL SAFETY TESTS** Electrical Safety	 IEC 61010-1:2010 including Amendment A1:2016 EN 61010-1:2010 including Amendment A1:2019 Excluding: Flammability tests Vicat softening test 11.6 Ingress protection (excluding only water and dust tests IPX1 to IPX9, IP5X, IP6X) 12.2 Ionizing radiation 12.3 Optical radiation 12.4 Microwave radiation 12.5 Sonic and ultrasonic pressure 12.6 Laser sources 13.2.3 High vacuum devices 14.8 Circuits limiting transient overvoltage 15.3 Interlock reliability test H Qualification of conformal coatings for protection against pollution	 A, B A, B

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used	Location Code
	6 ELECTRICAL SAFETY TESTS (cont'd)		
Measurement, control and laboratory use equipment – Laboratory equipment for the heating of materials	Electrical Safety	IEC 61010-2-010:2019 EN IEC 61010-2-010:2020	A, B
Measurement, control and laboratory use equipment – Automatic and semi-automatic Laboratory equipment for analysis and other purposes	Electrical Safety	IEC 61010-2-081:2019 EN IEC 61010-2-081:2020	A, B
Audio/video, information and communication technology equipment	Electrical Safety	IEC 62368-1:2023 IEC 62368-1:2018 IEC 62368-1:2014 EN IEC 62368-1:2024 including Amendment A11:2024 EN IEC 62368-1:2020 including Amendment A11:2020 EN 62368-1:2014 including Amendment A11:2017 Excluding: 5.4.1.10.2 Vicat test 5.4.4.6.5 Mandrel test 5.4.5.2, 5.4.5.3 Antenna terminal insulation 5.4.10.2.2 Impulse test 5.4.12.3 Compatibility of an insulating liquid 5.5.8 Insulation between the mains and an external circuit consisting of a coaxial cable 8.5.4.3, V.1.5 Equipment having an electromechanical device for destruction of media 8.5.5.2 High pressure lamps 10.2.1, 10.5.3, 10.6.4 Radiation energy tests (excluding only tests according to IEC 62471, IEC 60825-1, IEC 60825-2, IEC 60825-12, Xradiation, EN 50332-1 and EN 50332-2)	A, B

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used	Location Code
Audio/video, information and communication technology equipment	**6 ELECTRICAL SAFETY TESTS** (cont'd) Electrical Safety	Y.2 UV radiation F.3.7 Equipment IP rating marking (excluding only water and dust tests – IPX1 to IPX9, IP5X, IP6X) G.5.3.4 Test for transformers using fully insulated winding wire (FIW) G.5.4.3, G.5.4.4 – Motors – Running overload and locked-rotor overload tests G.8.2.2 Varistor overload test G.8.2.3 Temporary overvoltage test G.9.2, G.9.3 IC current limiters – Test programs G.10.3 G.10.6 Resistor tests G.13.6 Tests on coated printed wiring boards and coated components (conformal coatings) G.14 Coatings on component terminals G.15 Pressurized liquid filled components or LFC assemblies G.16.2, G.16.3 – IC that includes a capacitor discharge function (ICX) H Criteria for telephone ringing signals J.2, J.3 Insulated winding wires for use without interleaved insulation K.5 Safety interlock test – Fail safe K.6.2 Safety interlock: Mechanical endurance test K.7.2, K.7.3 Safety interlock: Switching device overload and endurance test M.7 Concentration of hydrogen gas M.8.2 Protection against internal ignition from external spark sources P.4.2 Metallized coatings and adhesives securing parts R Limited short-circuit test S.1, S.2, S.3, S.5, S.6 – Flammability tests U mechanical strength of CRTs and protection against the effects of implosion Y construction requirements for outdoor enclosures	A, B

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used	Location Code
	6 ELECTRICAL SAFETY TESTS (cont'd)		
Audio/video, information and Communication technology equipment	Electrical Safety - Safety aspects for DC power transfer through communication	IEC 62368-3:2017 EN IEC 62368-3:2020 Excluding: 6.3.1 RFT-C circuit limits 6.3.2 - RFT-V circuit limits	A, B
Electrical/Electronic products	Electrical Safety - Degrees of Protection provided by enclosures (IP Code)	IEC 60529:1989 including Amendments AMD1:1999 & AMD2:2013 EN 60529:1991 including Amendments A1:2000 & A2:2013 Excluding: water and dust tests - IPX1 to IPX9, IP5X, IP6X	A, B

Laboratory Facilities:	
Semi-Anechoic Chamber AC1 7.6 m (l) x 6.1 m (w) x 3.75 m (h) overall; 6.47 m (l) x 4.94 m (w) x 3.0 m (h) effective	A
Semi-Anechoic Chamber AC2 7.3 m (l) x 6.46 m (w) x 3.6 m (h) overall; 6.46 m (l) x 4.97 m (w) x 3.53 m (h) effective	A
Semi-anechoic Chamber AC3 3 m CISPR 16 compliant 9.0 m (l) x 6.1 m (w) x 5.7 m (h) overall; 8.45 m (l) x 5.08 m (w) x 5.65 m (h) effective	A
Semi-anechoic Chamber AC4 10 m CISPR 16 compliant 18.2 m (l) x 12.7 m (w) x 8.1 m (h) overall; 17.7 m (l) x 11.55 m (w) x 7.55 m (h) minimum effective Door Size: 4 m x 4 m Max Load: 20 tonne	A
Semi-anechoic Chamber AC5 7.3 m (l) x 7.1 m (w) x 4.15 m (h) overall 7.0m (l) x 6.8m (w) x 3.85 m (h) minimum effective	A
Semi-anechoic Chamber AC6 10 m CISPR 16 compliant 22.0 m (l) x 14.5 m (w) x 8.5 m (h) overall; 20.5 m (l) x 13.1 m (w) x 7.8 m (h) minimum effective Door Size: 5 m x 5 m Max Load: 50 tonne	B
Semi-anechoic Chamber AC7 CISPR 25 compliant 10.4 m (l) x 7.4 m (w) x 4.23 m (h) overall; 10.0 m (l) x 7.0 m (w) x 3.99 m (h) minimum effective; Door Size: 2.76 m (w) x 2.46 m (h) Max Load: 3.5 tonne	B
Screened Room SR1 4.85 m (l) x 3.34 m (w) x 3.0 m (h)	A
Screened Room SR2 5.9 m (l) x 3.9 m (w) x 2.9 m (h)	B
Vehicle Electrical Test Lab OBC Vehicle preparations and Transients	B
Reverberation Chamber RC1 7.0 m (l) × 4.6 m (w) × 3.2 m (h)	B
Dedicated Automotive Transient Laboratory, Auto 1, Auto 3 & Auto 4,Auto 5 & Auto 6	A
Dedicated High Voltage, ESD and Harmonics Laboratory, LAB2	A
Environmentally controlled labs for transient, ESD and Electrical Testing, LAB 3 Auto 1, Auto 3 & Auto 4,Auto 5 & Auto 6,	A

Laboratory Facilities: (cont'd)	
Max size of EUT: 4.0 m x 6.0 m x 4.0 m	A, B
Electrical Supplies: 240V 50/60/400 Hz up to 63 A 415V 50/60/400 Hz up to 125 A 110V 50/60/400 Hz up to 63 A 0 -– 15000 V DC	A, B

END