Schedule of Accreditation

issued by

United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

2498

Accredited to ISO/IEC 17025:2017

UTAC UK Ltd

Issue No: 038 **Issue date:** 24 September 2026

Vehicle Test Facilities
Millbrook
Bedford
MK45 2JQ

Contact: Jeanette Lancaster
Tel: +44 (0)1525 408402
E-Mail: jeanette.lancaster@utac.com
Website: www.utac.com

Testing performed at the above address only

DETAIL OF ACCREDITATION

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
PETROLEUM & PETROLEUM PRODUCTS	**PERFORMANCE TESTS**	Documented In-House Procedures and/or Standard Specifications involving the use of standard engines
Diesel	Injector nozzle coking	CEC-F-23-T-01(Peugeot XUD9) Issues 24, 24.1,25 and 26.1 CEC-F-98-08 (Peugeot DW10) Issues 6, 6.1, 6.2, 7, 8, 9, 10, 11,11.1, 12 and 13
Gasolines	Valve sticking of gasoline fuels	CEC-F-16-A-96 Issues 5.3, 5.4, 5.5, 5.6, 5.7, 5.8, 5.9, 6.0 and 8
	Deposit forming tendency on intake valve and in combustion chambers of gasoline engines	CEC-F-20-A-98 (MB M111) Issues 8, 12, 12.1, 12.2, 12.3, 12.4, 12.5, 12.6 and 12.7
MOTOR VEHICLES AUTOMOTIVE COMPONENTS AND EQUIPMENT RIGIDISED VEHICLES (VEHICLE BUCKS) AIRCRAFT SEATS	Frontal, rear, and side impact Simulation Using an acceleration Sled (Some tests include the use of anthropomorphic dummies)	EASA CS23.562 Amend 6 EASA CS25.562 Amend 27 EASA CS27.562 Amend 9 EASA CS29.562 Amend 10

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
Passenger Vehicles Occupant injury criteria Vehicle structural deformation / integrity Fuel system integrity Electrical safety (protection against electric shock) Electrolyte spillage evaluation Retention and integrity of the Rechargeable Energy Storage System (REESS	**Crash and Safety Tests**	
	Frontal Full width Impact	UN ECE R33 – 00 Series, 03 Supp UN ECE R137 – 04 Series, 00 Supp – Excluding Annex 10 FMVSS 208 (Vol 90 2025) FMVSS 305 (Vol 90 2025)
	Frontal 30° impact	FMVSS 208 (Vol 90 2025)
	Frontal Offset Frontal impact	UN ECE R94 – 05 Series, 01 Supp – Excluding Annex 12 FMVSS 208(Vol 90 2025)
	Side Impact	UN ECE R95 – 06 Series, 01 Supp – Excluding Annex 10 FMVSS 214 (Vol 87 2022) FMVSS 305 (Vol 90 2025)
	Pole Side Impact	UN ECE R135 – 02 Series, 03 Supp – Excluding Annex 6 FMVSS 214(Vol 87 2022)
	Rear Impact Acceleration – 0.1 to 2000g Velocity - 0.1 to 30m/s Temperature - +15 to +35ºC Time – 1ms to 6.5s Displacement / Deflection – 0.1mm to 12000mm Data sampling rate – 250 Hz to 0.5MHz Pressure – 0 to 6.9 bar Voltage - +/- 1000Volts	UN ECE R32 – 00 Series, 02 Supp UN ECE R34 – 04 Series, 00 Supp UN ECE R153 – 01 Series, 00 Supp – Excluding Annex 4 FMVSS 301 (Vol 78 2013) FMVSS 305 (Vol 90 2025)
Passenger Vehicles – Seats, Interior Fittings & Occupant Restraint Systems, including Event Data Recorder	Seat belt anchorage Time – 1ms to 6.5s Force – 0.1-300kN Temperature - +15 to +35ºC Displacement / Deflection – 0.1mm to 12000mm Data sampling rate – 250 Hz to 0.5MHz	UN ECE R14 – 09

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
AEROSPACE COMPONENTS AND EQUIPMENT AUTOMOTIVE COMPONENTS AND ASSEMBLIES TRAIN COMPONENTS AND ASSEMBLIES PLASTIC COMPONENTS AND PRODUCTS STRUCTURES, COMPONENTS AND FITTINGS	**ENVIRONMENTAL TESTS** (Non- explosive items)	Documented In-House Procedures, Customer Specifications, and International Standards
	CLIMATIC	
	HIGH /LOW TEMPERATURE (Constant & cyclic)	BS EN 60068-2-1: 1993(1994) BS EN 60068-2-1: 2007 BS EN 60068-2-1: 2025
	Max temp: 110 °C Min temp: -60 °C	BS EN 60068-2-2: 1993 BS EN 60068-2-2: 2007 BS EN 60068-2-2: 2025
	Max chamber working area: 11 m x 5 m x 4 m	
	HIGH TEMPERATURE	BS EN 60068-2-5: 2011 BS EN 60068-2-5: 2018 DEF STAN 00-35 Part 3 Issue 4 Chapter 3-02 Test CL2 DEF STAN 00-35 Part 3 Issue 4 Chapter 3-06 Test CL6 DEF STAN 00-35 Part 3 Issue 5 Test CL3 (Thermal Effects)
	(Solar Radiation) Thermal effects only Max temp: 125 °C Max power per controller: 1120 Wm^{-2} Radiation area: 8 m x 3 m	
	HIGH HUMIDITY (Steady state and Cyclic) Temp range: 20 °C to 60 °C Humidity range: 3 %RH to 98 %RH Max chamber working area: 11 m x 4.5 m x 4 m	BS EN 60068-2-78: 2013 IEC 68-2-56: 1998
	DYNAMIC	
	VIBRATION	BS EN 60068-2-6: 1996 BS EN 60068-2-6: 2008 BS EN 60068-2-64: 1995 BS EN 60068-2-64: 2008 BS EN 60068-2-64: 2008 A1:2019
	Ambient temperature	
	Electromagnetic vibrators - Sinusoidal & random spectra Frequency range: 5Hz to 2kHz Max thrust: 24kN (Vertical axis only)	

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
BATTERY VEHICLES COMPONENTS - REESS	Fire resistance testing	ECE R100.02, Supplement 5 Paragraphs 6.5 and 6.5 and Annex 8E ECE R100.03, Supplement 3 Paragraphs 6.5 and Annex 9E ECE R100.04 Paragraphs 6.5 and Annex 9E
	Mechanical shock	ECE R100.02, Supplement 5 Paragraph 6.4.1.2, 6.4.1.3 and Annex 8C ECE R100.03 supplement 3 Paragraph 6.4.1.2, 6.4.1.3 and Annex 9C ECE R100.04 Paragraph 6.4.1.2, 6.4.1.3 and Annex 9C
	Battery charging/discharging 20-1000V, 0-1400A	ECE R100 Revision 2 Amendment 5. Annex 8 Appendix 1 ECE R100.03 supplement 3 Annex 9 appendix 1 & 2; ECE R100.04 Annex 9 appendix 1 & 2
	Thermal shock and cycling. -40 to +90 °C	ECE R100.02, Supplement 5 Paragraph 6.3 and Annex 8B ECE R100.03 supplement 3 paragraph 6.3 & Annex 9B; ECE R100.04 Paragraph 6.3 and Annex 9B
	Mechanical Integrity (crush) - 100kN	ECE R100.02, Supplement 5 Paragraph 6.4.2.1.2, 6.4.2.2, 6.4.2.3 and Annex 8D ECE R100.03 supplement 3 Paragraphs 6.4.2.1.2, 6.4.2.2 , 6.4.2.3 & Annex 9D; ECE R100.04 Paragraphs 6.4.2.1.2, 6.4.2.2 , 6.4.2.3and Annex 9D

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
BATTERY VEHICLES COMPONENTS – REESS (cont'd)	Short Circuit. <=8000A, <=1200V	ECE R100.02, Supplement 5 Paragraph 6.6 and Annex 8F ECE R100.03, Supplement 3 Paragraph 6.6 and Annex 9F; ECE R100.04 Paragraph 6.6 and Annex 9F
	Overcharge protection 20-1000V, 0-1400A	ECE R100.02, Supplement 5 Paragraph 6.7 and Annex 8G ECE R100.03,Supplement 3 Paragraph 6.7 and Annex 9G ECE R100.04 Paragraph 6.7 and Annex 9G
	Over Discharge 20-1000V, 0-1400A	ECE R100.02, Supplement 5 Paragraph 6.8 and Annex 8H ECE R100.03 Supplement 3 Paragraph 6.8 and Annex 9H ECE R100.04 Paragraph 6.8 and Annex 9H
	Over Temperature 20-1000V, 0-1400A, -40 to +90 °C	ECE R100.02, Supplement 5 Paragraph 6.9 and Annex 8I ECE R100.03, Supplement 3 Paragraph 6.9 and Annex 9I ECE R100.04 Paragraph 6.9 and Annex 9I
	Isolation Resistance 0 to 2 GΩ	ECE R100.02, Supplement 5 Paragraph 5.1.3 and Annex 4A and 4B ECE R100.03, Supplement 3 Paragraph 5.1.3 and Annex 5A and 5B ECE R100.04 Paragraph 5.1.3 and Annex 5A and 5B;
	Overcurrent protection. 20-1000V, 0-1400A.	ECE R100.03 Supplement 3 Paragraph 6.10 and Annex 9J; ECE R100.04 Paragraph 6.10 and Annex 9J
	Chamber# 6 for REESS max size: 2.8 m x 3.5 m x 2.2 m	

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
VEHICLES AND VEHICLE COMPONENTS	Noise Testing	
TYRES	Approval of Tyres regarding rolling sound emissions of C Type tyres	UNECE Regulation 117-02 Annex 3
VEHICLES IN EU / UNECE CATEGORIES		
M – Passenger Vehicles N – Goods Vehicles L – Motorcycles	Vehicle Exterior Noise Tests (Noise level, vehicle speed and position)	UNECE Regulation 51-02 Annexes 3, 5, 6, 7 and 10 UNECE Regulation 51-03 Annexes 3, 4, 5, 6, and 7 UNECE Regulation 138-01 Annex 3 EU Regulation 540/2014 Annexes II, IV, V, VI, VII and VIII UNECE Regulation 41-05 Annex 3
M – Passenger Vehicles N – Goods Vehicles L - Motorcycles	Audible Warning (Horn)	UNECE Regulation 28-00 Part II
END		