


# Schedule of Accreditation

issued by

## United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

 <p><b>UKAS</b> CALIBRATION <b>28763</b></p> <p>Accredited to ISO/IEC 17025:2017</p>	<p><b>Precision Acoustics Ltd</b></p> <p>Issue No: 001    Issue date: 10 July 2025</p>	
	<p>Hampton Farm Business Park Higher Bockhampton Dorchester Dorset DT2 8QH</p>	<p>Contact: Mr David Bell / Mr Adam Pounder Tel: +44 (0) 1305 264669 E-Mail: david@acoustics.co.uk adam@acoustics.co.uk Website: <a href="https://www.acoustics.co.uk">https://www.acoustics.co.uk</a></p>
<p><b>Calibration performed at the above address only</b></p>		

### Calibration and Measurement Capability (CMC)

Measured Quantity Instrument or Gauge	Range	Expanded Measurement Uncertainty ( $k = 2$ )	Remarks
<p><b>ULTRASONICS</b></p> <p>Free field sensitivity of measuring hydrophones. End of cable loaded sensitivity of a hydrophone.</p>	<p>1 MHz to 12 MHz 13 MHz to 16 MHz 17 MHz to 20 MHz 21 MHz to 30 MHz</p>	<p>8.0 % 9.0 % 12 % 13 %</p>	<p>By comparison with a reference hydrophone in a laboratory tank in accordance with Section 12 BS EN 62127-2:2007 +A2:2017 IEC 62127-2:2007 Amd 2 Ed. 1.0: 2017 (Withdrawn)</p>
<p>END</p>			



28763

Accredited to  
ISO/IEC 17025:2017

**Schedule of Accreditation**  
issued by  
**United Kingdom Accreditation Service**  
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

**Precision Acoustics Ltd**  
**Issue No:** 001 **Issue date:** 10 July 2025

Calibration performed at main address only

**Appendix - Calibration and Measurement Capabilities**

**Introduction**

The definitive statement of the accreditation status of a calibration laboratory is the Accreditation Certificate and the associated Schedule of Accreditation. This Schedule of Accreditation is a critical document, as it defines the measurement capabilities, ranges and boundaries of the calibration activities for which the organisation holds accreditation.

**Calibration and Measurement Capabilities (CMCs)**

The capabilities provided by accredited calibration laboratories are described by the Calibration and Measurement Capability (CMC), which expresses the lowest measurement uncertainty that can be achieved during a calibration. If a particular device under calibration itself contributes significantly to the uncertainty (for example, if it has limited resolution or exhibits significant non-repeatability) then the uncertainty quoted on a calibration certificate will be increased to account for such factors.

The CMC is normally used to describe the uncertainty that appears in an accredited calibration laboratory's schedule of accreditation and is the uncertainty for which the laboratory has been accredited using the procedure that was the subject of assessment. The measurement uncertainty is calculated according to the procedures given in the GUM and is normally stated as an expanded uncertainty at a coverage probability of 95 %, which usually requires the use of a coverage factor of  $k = 2$ . An accredited laboratory is not permitted to quote an uncertainty that is smaller than the published measurement uncertainty in certificates issued under its accreditation.

**Expression of CMCs - symbols and units**

It should be noted that the percentage symbol (%) represents the number 0.01. In cases where the measurement uncertainty is stated as a percentage, this is to be interpreted as meaning percentage of the measurand. Thus, for example, a measurement uncertainty of 1.5 % means  $1.5 \times 0.01 \times q$ , where  $q$  is the quantity value.

The notation  $Q[a, b]$  stands for the root-sum-square of the terms between brackets:  $Q[a, b] = [a^2 + b^2]^{1/2}$