


Schedule of Accreditation

issued by

United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

 <p>UKAS REFERENCE MATERIALS 4589</p> <p>Accredited to ISO 17034:2016</p>	<p>Paragon Scientific Ltd</p> <p>Issue No: 041 Issue date: 15 April 2026</p>	
	<p>6 Prenton Way North Cheshire Trading Estate Prenton Wirral CH43 3DU</p>	<p>Contact: Rachael Stevens Tel: +44 (0)151 649 9955 E-Mail: paragon.sales@lgcgroup.com Website: www.lgcstandards.com/Paragon_Scientific</p>
Reference material production at the above address		

DETAIL OF ACCREDITATION

Matrix / Artefact	Property Value(s) / Identity / Characterisation Range	Characterisation Procedure / Technique	Type* (CRM / RM)
<p><u>Reference Materials with Viscosity Properties</u></p> <p>Base, blended oils, hydrocarbons and aqueous blends</p>	Kinematic viscosity	<p>Measurement by a single, primary, method at Paragon ASTM D2162</p> <p>Viscosity values at intermediate temperatures can be determined in accordance with ASTM D341</p> <p>Viscosity index can be calculated in accordance with ASTM D2270</p>	CRM
<p>Base, blended oils, hydrocarbons and aqueous blends</p>	Kinematic viscosity	<p>Measurement by a single, primary, method at Paragon ASTM D445</p> <p>Viscosity values at intermediate temperatures can be determined in accordance with ASTM D341</p> <p>Viscosity index can be calculated in accordance with ASTM D2270</p>	CRM
<p>Silicon Oils</p>	Kinematic viscosity	<p>Measurement by a single, primary, method at Paragon ASTM D445</p>	CRM
<p>Base, blended oils, hydrocarbons and aqueous blends</p>	Dynamic viscosity	<p>Measurement by a single, primary, method at Paragon ASTM D2162</p> <p>Viscosity values at intermediate temperatures can be determined in accordance with ASTM D341</p>	CRM



4589
Accredited to
ISO 17034:2016

Schedule of Accreditation
issued by
United Kingdom Accreditation Service
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

Paragon Scientific Ltd
Issue No: 041 Issue date: 15 April 2026

Reference material certification performed at main address only

Matrix / Artefact	Property Value(s) / Identity / Characterisation Range	Characterisation Procedure / Technique	Type* (CRM / RM)
<p><u>Reference Materials with Density Properties and Calculation of Relative Density (Specific Gravity)</u></p> <p>Base, blended oils and hydrocarbons and pure water</p> <p>Salt solutions</p> <p>Solvents</p> <p>Blended oils</p> <p>Silicon Oils</p>	<p>0.6 g/ml to 1.2 g/ml</p> <p>1.25 g/ml to 1.30 g/ml</p> <p>1.17 g/ml to 1.65 g/ml</p> <p>0.6 g/ml to 1.2 g/ml</p> <p>0.9 g/ml to 1.0 g/ml</p>	<p>Measurement by a single, primary, method at Paragon ASTM D1480</p> <p>Calculation of Relative Density (Specific Gravity) from ASTM D1480 Density by division of Density by the Density of Water at the Specified Water Reference Temperature.</p> <p>Note: Relative Density (Specific Gravity) has no units by definition.</p> <p>Measurement by a method specific, interlaboratory study ASTM D4052 IP365 ISO12185</p> <p>Measurement by a single, primary, method at Paragon ASTM D1480</p>	<p>CRM</p> <p>CRM</p> <p>CRM</p>
<p><u>Ethanol/Water Reference Standards.</u></p> <p>Density in air at 20 °C Alcoholic Strength (%ABV)</p>	<p>0.8857 g/ml to 0.9912 g/ml</p>	<p>Measurement by a single, primary method at Paragon - ASTM D1480 (modified)</p> <p>Corresponding to 70% to 5% Ethanol by Volume taken as the % alcohol by volume corresponding to that density in air from the Official Laboratory Alcohol Table (RDC80/264/04), Issued under the authority of the UK HM Customs & Excise.</p>	<p>CRM</p>



4589
Accredited to
ISO 17034:2016

Schedule of Accreditation
issued by
United Kingdom Accreditation Service
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

Paragon Scientific Ltd
Issue No: 041 Issue date: 15 April 2026

Reference material certification performed at main address only

Matrix / Artefact	Property Value(s) / Identity / Characterisation Range	Characterisation Procedure / Technique	Type* (CRM / RM)
<u>Reference Materials with Refractive Index Properties</u> Base and Blended Hydrocarbons	Refractive index values of 1.33 to 1.65 at 15 °C, 20 °C, 25 °C and 30 °C	Measurement by a single, primary, method at Paragon Measurement using digital refractometer	CRM
<u>Certified Reference Materials with Flash Point Properties</u> Blended oils	Flash point, Pensky Marten closed cup	Measurement by a method specific, interlaboratory study ASTM D93 Procedure A & B IP 34 ISO 2719	CRM
Blended oils	Flash point, Cleveland open cup	Measurement by a method specific, interlaboratory study ASTM D92 IP36 ISO 2592 EN 2592	CRM
<u>Certified Reference Materials with Flash Point Properties</u> Blended oils	Flash point, Pensky Marten closed cup	Measurement by a single, primary, method at Paragon ASTM D93 Procedure A & B IP 34 ISO 2719	CRM
Blended oils	Flash Point, Cleveland open cup	Measurement by a single, primary, method at Paragon ASTM D92 IP36 ISO 2592 EN 2592	CRM



4589
Accredited to
ISO 17034:2016

Schedule of Accreditation
issued by
United Kingdom Accreditation Service
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

Paragon Scientific Ltd
Issue No: 041 Issue date: 15 April 2026

Reference material certification performed at main address only

Matrix / Artefact	Property Value(s) / Identity / Characterisation Range	Characterisation Procedure / Technique	Type* (CRM / RM)
<u>Certified Reference Materials with Pour Point Properties</u> Blended oils	Pour point	Measurement by a method specific, interlaboratory study ASTM D97 IP 15 ISO 3016 BS 2000: Part 15	CRM
<u>Certified Reference Materials with Cloud Point Properties</u> Blended oils	Cloud point	Measurement by a method specific, interlaboratory study ASTM D2500 IP 219 ISO 3015 EN 23015	CRM
<u>Certified Reference Materials with Cold Filter Plugging Point Properties</u> Blended oils	Cold Filter Plugging Point (CFPP)	Measurement by a method specific, interlaboratory study ASTM D6371 IP 309 EN 116 BS 2000: Pt 309	CRM
<u>Certified Reference Materials with Distillation Properties</u> Blended oils Blended oils	Distillation Properties Distillation Properties	Measurement by a method specific, interlaboratory study ASTM D86 IP 123 ISO 3405 EN ISO 3405 Measurement by a single, Primary gravimetric method at Paragon ASTM D86	CRM CRM



4589
Accredited to
ISO 17034:2016

Schedule of Accreditation
issued by
United Kingdom Accreditation Service
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

Paragon Scientific Ltd
Issue No: 041 Issue date: 15 April 2026

Reference material certification performed at main address only

Matrix / Artefact	Property Value(s) / Identity / Characterisation Range	Characterisation Procedure / Technique	Type* (CRM / RM)
<u>Reference Materials with Colour Properties</u>			
Blended oils and hydrocarbons	ASTM colour	Measurement by a single, primary, method at Paragon (spectrophotometry) ASTM D6045 ASTM D1500	CRM
Blended oils and hydrocarbons	Saybolt colour	Measurement by a single, primary, definitive method at Paragon (spectrophotometry) ASTM D6045 ASTM D156	CRM
Blended oils and hydrocarbons	Gardner colour	Measurement by a single, primary, definitive method at Paragon (spectrophotometry) ASTM D6166 ASTM D1544	CRM
Aqueous solutions	Platinum-Cobalt colour	Measurement by a single, primary, method at Paragon (spectrophotometry)	CRM
<u>Reference Materials with Other Properties</u>			
Jet A1 Kerosene	Abel Flash Point	Measurement by a method specific, interlaboratory study IP 170 ISO 13736	CRM
Jet A1 Kerosene	Acidity in Aviation Turbine Fuel	Measurement by a method specific, interlaboratory study ASTM D3242 IP354	CRM
Jet A1 Kerosene	Hydrocarbon Types in Liquid Petroleum Products by Fluorescent Indicator Adsorption	Measurement by a method specific, interlaboratory study ASTM D1319	CRM
Jet A1 Kerosene	Aniline Point of Petroleum Products and Hydrocarbon Solvents	Measurement by a method specific, interlaboratory study ASTM D61 IP2	CRM



Schedule of Accreditation
issued by
United Kingdom Accreditation Service
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

Paragon Scientific Ltd
Issue No: 041 Issue date: 15 April 2026

Reference material certification performed at main address only

Matrix / Artefact	Property Value(s) / Identity / Characterisation Range	Characterisation Procedure / Technique	Type* (CRM / RM)
Jet A1 Kerosene	Freezing Point of Aviation Fuels	Measurement by a method specific, interlaboratory study ASTM D2386 IP16	CRM
Jet A1 Kerosene	Flash Point by Tag Closed Cup Tester	Measurement by a method specific, interlaboratory study ASTM D56	CRM
Jet A1 Kerosene	Smoke Point of Kerosene and Aviation Turbine Fuel	Measurement by a method specific, interlaboratory study ASTM D1322	CRM
Jet A1 Kerosene	(Thiol Mercaptan) Sulphur in Gasoline, Kerosene, Aviation Turbine, and Distillate Fuels (Potentiometric Method)	Measurement by a method specific, interlaboratory study ASTM D3227 IP342	CRM
Base Oil	Total Acid Number (TAN)	Measurement by single primary method at Paragon in accordance with ASTM D664	CRM
Base Oil	Total Base Number (TBN)	Measurement by single primary method at Paragon in accordance with ASTM D2896	CRM
Hydrocarbons	Sulfur Content	Measurement by Gravimetric Preparation	CRM
Iodine unsaturated Properties	Iodine value per 100 g	Measurement by single primary method at Paragon (Automatic titrator) in accordance with BS EN 14111 and BS EN ISO 3961	CRM
Ester Properties	Ester content in FAME 90% m/m to 100% m/m	Measurement by single primary method at Paragon (Gas chromatography) in accordance with BS EN 14103 and BS EN14103:2011 (superseded)	CRM
Linolenic Properties	Linolenic acid methyl ester content 1% m/m to 15% m/m	Measurement by single primary method at Paragon (Gas chromatography) in accordance with BS EN 14103 and BS EN14103:2011 (superseded)	CRM



4589
Accredited to
ISO 17034:2016

Schedule of Accreditation
issued by
United Kingdom Accreditation Service
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

Paragon Scientific Ltd
Issue No: 041 Issue date: 15 April 2026

Reference material certification performed at main address only

Matrix / Artefact	Property Value(s) / Identity / Characterisation Range	Characterisation Procedure / Technique	Type* (CRM / RM)
<u>Reference Materials with pH properties</u> pH buffer solutions	pH4 to pH10	Measurement by single primary method at Paragon in accordance with ASTM E70	CRM
<u>Smoke Point Reference Fuel Blends</u> 2,2,4Trimethylpentane / Toluene mixtures from 60 % to 100 % v/v 2,2,4-trimethylpentane	Blends corresponding to Smoke Points in the range 14.7 mm to 42.8 mm at 101.3 kPa. Test methods ASTM D1322 and IP598.	% v/v Blends by Gravimetric Preparation of Blends with confirmatory analysis by ASTM D4052.	CRM
Reference Materials with Iodine unsaturated Properties	Iodine value per 100 g	Measurement by single primary method at Paragon (Automatic titrator) in accordance with BS EN 14111 and BS EN ISO 3961	CRM
Reference Materials with Ester Properties	Ester content in FAME 90% m/m to 100% m/m	Measurement by single primary method at Paragon (Gas chromatography) in accordance with BS EN 14103 and BS EN14103:2011 (superseded)	CRM
Reference Materials with Linolenic Properties	Linolenic acid methyl ester content 1% m/m to 15% m/m	Measurement by single primary method at Paragon (Gas chromatography) in accordance with BS EN 14103 and BS EN14103:2011 (superseded)	CRM
<u>Reference Materials with Electrical Conductivity properties</u> Electrical Conductivity Solutions	2 μ S/cm to 500,000 μ S/cm	Measurement by single primary method at Paragon using conductivity meter	CRM



Schedule of Accreditation
issued by
United Kingdom Accreditation Service
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

Paragon Scientific Ltd
Issue No: 041 Issue date: 15 April 2026

Reference material certification performed at main address only

Matrix / Artefact	Property Value(s) / Identity / Characterisation Range	Characterisation Procedure / Technique	Type* (CRM / RM)
<u>Reference Materials with Vapour pressure properties</u>			
Hydrocarbons & Fuels	Total Vapour Pressure	Measurement by a method specific, interlaboratory study to ASTM D5191	CRM
Hydrocarbons & Fuels	Dry Vapour Pressure Equivalent		CRM

Flexible Scope

The laboratory is accredited to ISO 17034:2016 for the production of reference materials in accordance with the standards highlighted in the schedule. This may also include new versions of existing accredited standard test methods to be introduced in accordance with documented in-house procedure QA018, providing that:

- (1) The method or standard does not introduce new principles of measurement.
- (2) The method or standard does not require measurements to be made outside the parametric boundaries defined within the standard specifications already accredited and detailed within this Schedule of Accreditation.

Information about flexible scopes of accreditation is available in UKAS document GEN 4 and EA document EA-2/15.

END

***Type**

CRM = Certified Reference Material(s)

RM = Reference Material(s)

Refer to ISO 17034 for full definitions