

# Schedule of Accreditation

issued by

## United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK



8427

Accredited to  
ISO/IEC 17025:2017

### Gilson Scientific Limited

Issue No: 012 Issue date: 27 February 2024

3B Humphrys Road  
Woodside Estate  
Dunstable  
LU5 4TP

Contact: Mrs Fiona Saunders  
Tel: +44 (0) 1582 399475  
E-Mail: fsaunders@gilson.com  
Website: www.gilson.com

Calibration performed by the Organisations at the locations specified below

#### Locations covered by the organisation and their relevant activities

##### Laboratory locations:

Location details	Activity	Location code
<b>Address</b> 3B Humphrys Road Woodside Estate Dunstable LU5 4TP  <b>Local contact</b> Fiona Saunders	Volume	A

##### Site activities performed away from the locations listed above:

Location details	Activity	Location code
Customers premises  The customers' site or premises must be suitable for the nature of the particular calibrations undertaken and will be the subject of contract review arrangements between the laboratory and the customer.	Volume	Site



8427  
Accredited to  
ISO/IEC 17025:2017

**Schedule of Accreditation**  
issued by  
**United Kingdom Accreditation Service**  
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

**Gilson Scientific Limited**  
**Issue No: 012 Issue date: 27 February 2024**

Calibration performed by the Organisation at the locations specified

Calibration and Measurement Capability (CMC)

Measured Quantity Instrument or Gauge	Range	Expanded Measurement Uncertainty ( $k = 2$ )	Remarks	Location Code
VOLUME of liquids (See Note 1)  For water delivered from a POVA.	Nominal volume  Single Channel Pipettes 0.1 µl to 0.2 µl 0.2 µl to 2 µl 2 µl to 10 µl 10 µl to 20 µl 20 µl to 100 µl 100 µl to 200 µl 200 µl to 1000 µl 1000 µl to 5000 µl 5000 µl to 12500 µl  12.5 ml to 25 ml 25 ml to 50 ml 50 ml to 100 ml  Multi Channel Pipettes 1 µl to 20 µl 20 µl to 300 µl 300 µl to 600 µl 600 µl to 1200 µl	  0.06 µl 0.09 µl 0.15 µl 0.23 µl 0.76 µl 1.51 µl 3.67 µl 4.84 µl 5.31 µl  0.029 ml 0.032 ml 0.032 ml  0.19 µl 0.50 µl 0.90 µl 1.8 µl	  Note 1. For water delivered from POVA (piston and/or plunger operated volumetric apparatus) using procedures agreed with UKAS.  Note 2. To include multi- channel instruments of up to 12 channels simultaneously calibrated.  Gravimetric method  3 volumes 10 readings (as specified in ISO 8655)  3 volumes 5 readings  2 volumes 4 readings	  A and Site   A  A and Site
END				



8427  
Accredited to  
ISO/IEC 17025:2017

**Schedule of Accreditation**  
issued by  
**United Kingdom Accreditation Service**  
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

**Gilson Scientific Limited**  
**Issue No: 012 Issue date: 27 February 2024**

Calibration performed by the Organisation at the locations specified

**Appendix - Calibration and Measurement Capabilities**

**Introduction**

The definitive statement of the accreditation status of a calibration laboratory is the Accreditation Certificate and the associated Schedule of Accreditation. This Schedule of Accreditation is a critical document, as it defines the measurement capabilities, ranges and boundaries of the calibration activities for which the organisation holds accreditation.

**Calibration and Measurement Capabilities (CMCs)**

The capabilities provided by accredited calibration laboratories are described by the Calibration and Measurement Capability (CMC), which expresses the lowest measurement uncertainty that can be achieved during a calibration. If a particular device under calibration itself contributes significantly to the uncertainty (for example, if it has limited resolution or exhibits significant non-repeatability) then the uncertainty quoted on a calibration certificate will be increased to account for such factors.

The CMC is normally used to describe the uncertainty that appears in an accredited calibration laboratory's schedule of accreditation and is the uncertainty for which the laboratory has been accredited using the procedure that was the subject of assessment. The measurement uncertainty is calculated according to the procedures given in the GUM and is normally stated as an expanded uncertainty at a coverage probability of 95 %, which usually requires the use of a coverage factor of  $k = 2$ . An accredited laboratory is not permitted to quote an uncertainty that is smaller than the published measurement uncertainty in certificates issued under its accreditation.

**Expression of CMCs - symbols and units**

It should be noted that the percentage symbol (%) represents the number 0.01. In cases where the measurement uncertainty is stated as a percentage, this is to be interpreted as meaning percentage of the measurand. Thus, for example, a measurement uncertainty of 1.5 % means  $1.5 \times 0.01 \times q$ , where  $q$  is the quantity value.

The notation  $Q[a, b]$  stands for the root-sum-square of the terms between brackets:  $Q[a, b] = [a^2 + b^2]^{1/2}$