

# Schedule of Accreditation

issued by

## United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK



8747

Accredited to  
ISO/IEC 17025:2017

### DWK Life Sciences Limited

Issue No: 008

Issue date: 14 January 2022

4, Gordon Banks Drive  
Trentham Lakes North  
Stoke on Trent  
ST4 4TW  
United Kingdom

Contact: Mr Kevin Marshall  
Tel: +44 (0)1782 940422  
Fax: +44 (0)1782 940436  
E-Mail: Kevin.Marshall@dwk.com  
Website: www.dwk.com

Calibration performed at the above address only

#### Calibration and Measurement Capability (CMC)

Measured Quantity Instrument or Gauge	Range	Expanded Measurement Uncertainty ( $k = 2$ )	Remarks
Volumetric Flasks	5 ml 10 ml 20 ml 25 ml 50 ml 100 ml 200 ml 250 ml 500 ml 1000 ml 2000 ml	0.012 ml 0.012 ml 0.018 ml 0.018 ml 0.025 ml 0.04 ml 0.05 ml 0.08 ml 0.08 ml 0.15 ml 0.25 ml	Calibrated by gravimetric method
Type 1 Tall Form Cylinders	5 ml 10 ml 25 ml 50 ml 100 ml 250 ml 500 ml 1000 ml 2000 ml	0.02 ml 0.04 ml 0.10 ml 0.15 ml 0.20 ml 0.40 ml 0.80 ml 1.00 ml 2.00 ml	Calibrated by gravimetric method
END			



8747  
Accredited to  
ISO/IEC 17025:2017

**Schedule of Accreditation**  
issued by  
**United Kingdom Accreditation Service**  
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR UK

**DWK Life Sciences Limited**  
**Issue No:** 008    **Issue date:** 14 January 2022

Calibration performed at main address only

**Appendix - Calibration and Measurement Capabilities**

**Introduction**

The definitive statement of the accreditation status of a calibration laboratory is the Accreditation Certificate and the associated Schedule of Accreditation. This Schedule of Accreditation is a critical document, as it defines the measurement capabilities, ranges and boundaries of the calibration activities for which the organisation holds accreditation.

**Calibration and Measurement Capabilities (CMCs)**

The capabilities provided by accredited calibration laboratories are described by the Calibration and Measurement Capability (CMC), which expresses the lowest measurement uncertainty that can be achieved during a calibration. If a particular device under calibration itself contributes significantly to the uncertainty (for example, if it has limited resolution or exhibits significant non-repeatability) then the uncertainty quoted on a calibration certificate will be increased to account for such factors.

The CMC is normally used to describe the uncertainty that appears in an accredited calibration laboratory's schedule of accreditation and is the uncertainty for which the laboratory has been accredited using the procedure that was the subject of assessment. The measurement uncertainty is calculated according to the procedures given in the GUM and is normally stated as an expanded uncertainty at a coverage probability of 95 %, which usually requires the use of a coverage factor of  $k = 2$ . An accredited laboratory is not permitted to quote an uncertainty that is smaller than the published measurement uncertainty in certificates issued under its accreditation.

**Expression of CMCs - symbols and units**

It should be noted that the percentage symbol (%) represents the number 0.01. In cases where the measurement uncertainty is stated as a percentage, this is to be interpreted as meaning percentage of the measurand. Thus, for example, a measurement uncertainty of 1.5 % means  $1.5 \times 0.01 \times q$ , where  $q$  is the quantity value.

The notation  $Q[a, b]$  stands for the root-sum-square of the terms between brackets:  $Q[a, b] = [a^2 + b^2]^{1/2}$