

Schedule of Accreditation

issued by

United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

 <p>0068</p> <p>Accredited to ISO/IEC 17025:2017</p>	<p>Yorkshire Precision Gauges Ltd</p> <p>Issue No: 031 Issue date: 08 March 2024</p>	
	<p>Cuckoo Lane Hatfield Doncaster DN7 6QF</p>	<p>Contact: Patrick Gregory Tel: +44 (0)1302-840303 E-Mail: Calibration@yppg.co.uk Website: www.yppg.co.uk</p>
<p>Calibration performed at the above address only</p>		

Calibration and Measurement Capability (CMC)

Measured Quantity Instrument or Gauge	Range	Expanded Measurement Uncertainty ($k = 2$)	Remarks
<p>RANGE IN MILLIMETRES AND UNCERTAINTY IN MICROMETRES UNLESS OTHERWISE STATED</p>			
LENGTH			
Thread measuring cylinders Including specials	0.1 to 5 diameter	0.50	Calibration as BS 5590 by comparison to reference standards
Plain plug gauges (parallel), cylindrical setting standards, gear measuring cylinders and rollers	0.5 to 50 diameter	0.50	By comparison to reference standards
	50 to 100	0.80	
	100 to 150	1.0	
Plain ring gauges (parallel) and setting standards	3 to 14 diameter	1.0	By comparison to reference standards
	14 to 50	1.0	
	50 to 100	1.0	
Plain gap gauges (parallel)	0.5 to 100	3.0	By comparison to reference standards
	100 to 200	5.0	
	200 to 300	10	
Barrel type depth gauges and feelers gauges (laboratories own manufacture)	0.5 to 100	1.0	By comparison to reference standards using documented in- house methods.
FORM			
Roundness (in support of other measurements)	External] 0.35 on radius	Calibration as BS 3730 using a roundness measuring machine
	Internal		
<p>END</p>			



0068
Accredited to
ISO/IEC 17025:2017

Schedule of Accreditation
issued by
United Kingdom Accreditation Service
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

Yorkshire Precision Gauges Ltd
Issue No: 031 Issue date: 08 March 2024

Calibration performed at main address only

Appendix - Calibration and Measurement Capabilities

Introduction

The definitive statement of the accreditation status of a calibration laboratory is the Accreditation Certificate and the associated Schedule of Accreditation. This Schedule of Accreditation is a critical document, as it defines the measurement capabilities, ranges and boundaries of the calibration activities for which the organisation holds accreditation.

Calibration and Measurement Capabilities (CMCs)

The capabilities provided by accredited calibration laboratories are described by the Calibration and Measurement Capability (CMC), which expresses the lowest measurement uncertainty that can be achieved during a calibration. If a particular device under calibration itself contributes significantly to the uncertainty (for example, if it has limited resolution or exhibits significant non-repeatability) then the uncertainty quoted on a calibration certificate will be increased to account for such factors.

The CMC is normally used to describe the uncertainty that appears in an accredited calibration laboratory's schedule of accreditation and is the uncertainty for which the laboratory has been accredited using the procedure that was the subject of assessment. The measurement uncertainty is calculated according to the procedures given in the GUM and is normally stated as an expanded uncertainty at a coverage probability of 95 %, which usually requires the use of a coverage factor of $k = 2$. An accredited laboratory is not permitted to quote an uncertainty that is smaller than the published measurement uncertainty in certificates issued under its accreditation.

Expression of CMCs - symbols and units

It should be noted that the percentage symbol (%) represents the number 0.01. In cases where the measurement uncertainty is stated as a percentage, this is to be interpreted as meaning percentage of the measurand. Thus, for example, a measurement uncertainty of 1.5 % means $1.5 \times 0.01 \times q$, where q is the quantity value.

The notation $Q[a, b]$ stands for the root-sum-square of the terms between brackets: $Q[a, b] = [a^2 + b^2]^{1/2}$