


Schedule of Accreditation

issued by

United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

 <p>UKAS CALIBRATION</p> <p>0583</p> <p>Accredited to ISO/IEC 17025:2017</p>	<p>Western Pegasus Ltd</p> <p>Issue No: 015 Issue date: 23 September 2021</p>	
	<p>Unit 5 747751 Warwick Road Tyseley Birmingham B11 2HA</p>	<p>Contact: Gary Adams Tel: +44 (0)121-706 1231 Fax: +44 (0)121-706 8425 E-Mail: gary.adams@westpeg.com Website: www.westpeg.com</p>
<p>Calibration performed at the above address only</p>		

DETAIL OF ACCREDITATION

Measured Quantity Instrument or Gauge	Range	Expanded Measurement Uncertainty ($k=2$)	Remarks
<p>RANGE IN MILLIMETERS AND UNCERTAINTY IN MICROMETRES UNLESS OTHERWISE STATED</p>			
SPUR/HELICAL MASTER GEARS			
Bore Diameter	11 to 50 50 to 100	1.0 2.5	Horizontal measuring machine and reference setting standards.
Tip Diameter	25 to 100 100 to 200	1.0 3.5	Horizontal measuring machine and reference setting standards.
Dimension Over/Pins (M_{dr})	25 to 100 100 to 200	5.0 7.5	Horizontal measuring machine or floating carriage micrometer and reference setting standards.
Profile total deviation (F_{α})	Overworking length of tooth	1.5 to 2.5 depending upon size	CNC gear measuring machine
Helix (Lead) total deviation (F_{β})	0 to 50 face width 50 to 100 face width	1.5 2.5	CNC gear measuring machine (with a maximum of 45° helix angle)
Radial Runout of Tooth Space (F_r)	50 to 100	1.0	CNC gear measuring machine
Single pitch (f_p)	25 to 200 reference circle diameter	1.0	CNC gear measuring machine
Pitch difference (f_u)	25 to 200	1.0	CNC gear measuring machine
Cumulative pitch (F_p)	25 to 200 reference circle diameter	3.5	CNC gear measuring machine
<p>RANGE IN MILLIMETERS AND UNCERTAINTY IN MICROMETRES UNLESS OTHERWISE STATED</p>			



0583
Accredited to
ISO/IEC 17025:2017

Schedule of Accreditation
issued by
United Kingdom Accreditation Service
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

Western Pegasus Ltd

Issue No: 015 Issue date: 23 September 2021

Calibration performed at main address only

Measured Quantity Instrument or Gauge	Range	Expanded Measurement Uncertainty ($k=2$)		Remarks
SPLINE GAUGES, INVOLUTE				
Spur and helical external including Taper Masters				
Major Diameter	5 to 100 100 to 200	1.0 3.5		Horizontal measuring machine and reference setting standards.
Dimensions over pins- spur gauges (Mdr)	From 5 up to 100 Above 100 up to 200	2.7 3.5		Horizontal measuring machine or floating carriage micrometer and reference setting standards.
Profile total deviation(F_a)	Over working Length of Tooth	1.5 to 2.5 depending upon size		CNC gear measuring machine
Helix (Lead) total deviation(F_β)	50 face width 50 up to 100 face width	1.5 2.5		CNC gear measuring machine
Single Pitch (f_p)	5 to 200 diameter	1.0		CNC gear measuring machine
Pitch difference (f_u)	5 to 200 diameter	1.0		CNC gear measuring machine
Cumulative Pitch (F_p)	5 to 200 diameter	3.5		CNC gear measuring machine
Spur and helical Internal				
Minor diameter	12 to 100 100 to 200	Even teeth 2.5 3.5	Odd teeth 3.5 5.0	Horizontal measuring machine or floating carriage micrometer and reference setting standards.
Dimension between pins- spur (Mdk)	12 to 100 100 to 200	2.7 5.0		Horizontal measuring machine and reference setting standards.
Dimension between balls- helical (Mdr)	12 to 100 diameter 100 to 200 diameter	5.0 7.5		Horizontal measuring machine and reference setting standards.
Profile total deviation(F_a)	Over working length of tooth	1.5 to 2.5 depending upon size		CNC gear measuring machine
Helix (Lead) total deviation(F_β)	0 to 50 face width	1.5 to 2.5 depending upon size		CNC gear measuring machine
Single pitch (f_p)	12 to 200 diameter	1.0		CNC gear measuring machine
Pitch difference (f_u)	12 to 200 diameter	1.0		CNC gear measuring machine
Cumulative pitch (F_p)	12 to 200 diameter	3.5		CNC gear measuring machine

RANGE IN MILLIMETERS AND UNCERTAINTY IN MICROMETRES
UNLESS OTHERWISE STATED



0583
Accredited to
ISO/IEC 17025:2017

Schedule of Accreditation
issued by
United Kingdom Accreditation Service
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

Western Pegasus Ltd

Issue No: 015 Issue date: 23 September 2021

Calibration performed at main address only

Measured Quantity Instrument or Gauge	Range	Expanded Measurement Uncertainty ($k=2$)		Remarks
SPLINE GAUGES STRAIGHT SIDED				
Plugs and rings				
Major diameter (plug)	10 to 100 diameter	1.0		Horizontal measuring machine and reference setting standards.
	100 to 200 diameter	3.5		
Minor diameter (plug)	10 to 100 diameter	1.0		Horizontal measuring machine and reference setting standards.
	100 to 200 diameter	3.5		
Major Diameter (ring)	12 to 50 diameter	Even Teeth	Odd Teeth	Horizontal measuring machine and reference setting standards.
	50 to 100 diameter	2.5	3.5	
	100 to 200 diameter	3.5	5.0	
Minor Diameter (ring)	12 to 50 diameter	5.0	7.5	Horizontal measuring machine and reference setting standards.
	50 to 100 diameter	2.5	3.5	
	100 to 200 diameter	3.5	5.0	
Spline Width	2 to 20	1.0		Gauge blocks
Helix (Lead) total deviation(F_{β})	0 to 50 face width	1.5		CNC gear measuring machine
	50 up to 100 face width	2.5		
Single pitch (f_p)	30 to 200	1.0		CNC gear measuring machine
Pitch difference (f_u)	30 to 200	1.0		CNC gear measuring machine
Cumulative pitch (F_p)	30 to 200	3.5		CNC gear measuring machine

RANGE IN MILLIMETERS AND UNCERTAINTY IN MICROMETRES
UNLESS OTHERWISE STATED



0583
Accredited to
ISO/IEC 17025:2017

Schedule of Accreditation
issued by
United Kingdom Accreditation Service
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

Western Pegasus Ltd
Issue No: 015 Issue date: 23 September 2021

Calibration performed at main address only

Measured Quantity Instrument or Gauge	Range	Expanded Measurement Uncertainty ($k=2$)		Remarks
SERRATION GAUGES STRAIGHT SIDED as BS 2059 (excluding taper serrations)				
Plugs and rings				
Major diameter (plug)	6 to 100 diameter 100 to 150 diameter	1.0 3.5		Horizontal measuring machine or floating carriage micrometer and reference setting standards.
Minor diameter (ring)	6 to 100 diameter 100 to 150 diameter	Even Teeth 2.5 3.5	Odd Teeth 3.5 5.0	Horizontal measuring machine and reference setting standards.
Dimension over pins (Mdk)	6 to 75 diameter 75 to 150 diameter	1.0 3.5		Horizontal measuring machine and reference setting standards.
Dimension under pins (Mdk)	6 to 100 diameter 100 to 150 diameter	2.5 5.0		Horizontal measuring machine and reference setting standards.
Serration angle	13 to 25 diameter 25 to 75 diameter 75 to 150 diameter	20 minutes of arc 15 minutes of arc 10 minutes of arc		CNC gear measuring machine
Single pitch (f_p)	0 to 50 face width 50 to 100 face width	1.0 2.5		CNC gear measuring machine
Pitch difference (f_u)	6 to 150 diameter	1.0		CNC gear measuring machine
Cumulative pitch (F_p)	6 to 150 diameter	3.5		CNC gear measuring machine
END				



0583
Accredited to
ISO/IEC 17025:2017

Schedule of Accreditation
issued by
United Kingdom Accreditation Service
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

Western Pegasus Ltd
Issue No: 015 **Issue date:** 23 September 2021

Calibration performed at main address only

Appendix - Calibration and Measurement Capabilities

Introduction

The definitive statement of the accreditation status of a calibration laboratory is the Accreditation Certificate and the associated Schedule of Accreditation. This Schedule of Accreditation is a critical document, as it defines the measurement capabilities, ranges and boundaries of the calibration activities for which the organisation holds accreditation.

Calibration and Measurement Capabilities (CMCs)

The capabilities provided by accredited calibration laboratories are described by the Calibration and Measurement Capability (CMC), which expresses the lowest measurement uncertainty that can be achieved during a calibration. If a particular device under calibration itself contributes significantly to the uncertainty (for example, if it has limited resolution or exhibits significant non-repeatability) then the uncertainty quoted on a calibration certificate will be increased to account for such factors.

The CMC is normally used to describe the uncertainty that appears in an accredited calibration laboratory's schedule of accreditation and is the uncertainty for which the laboratory has been accredited using the procedure that was the subject of assessment. The measurement uncertainty is calculated according to the procedures given in the GUM and is normally stated as an expanded uncertainty at a coverage probability of 95 %, which usually requires the use of a coverage factor of $k = 2$. An accredited laboratory is not permitted to quote an uncertainty that is smaller than the published measurement uncertainty in certificates issued under its accreditation.

Expression of CMCs - symbols and units

It should be noted that the percentage symbol (%) represents the number 0.01. In cases where the measurement uncertainty is stated as a percentage, this is to be interpreted as meaning percentage of the measurand. Thus, for example, a measurement uncertainty of 1.5 % means $1.5 \times 0.01 \times q$, where q is the quantity value.

The notation $Q[a, b]$ stands for the root-sum-square of the terms between brackets: $Q[a, b] = [a^2 + b^2]^{1/2}$