

Schedule of Accreditation

issued by

United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK



10333

Accredited to
ISO/IEC 17025:2017

Calibra Technology Ltd

Issue No: 006 Issue date: 19 September 2023

Unit 7, Meridian Buildings
Buckingway Business Park
Swavesey
Cambridgeshire
CB24 4AE

Contact: Mr Andrew Burston
Tel: +44 (0)1954 231917
Fax: +44 (0)1954 602415
E-Mail: enquiries@calibratechnology.com
Website: www.calibratechnology.com

Calibration performed at the above address only

Calibration and Measurement Capability (CMC)

Measured Quantity Instrument or Gauge	Range	Expanded Measurement Uncertainty ($k = 2$)	Remarks
FLOW - Hydrocarbon oils			
Calibration of Coriolis flow meters	3 g/min to 400 g/min	(0.0077 + 2.3 / Q_m) %	Gravimetric method at temperatures between ambient and 28 °C
	400 g/min to 3000 g/min	(0.0107 + 7.4 / Q_m) %	
Calibration of mass flow meters	3 g/min to 3000 g/min	(0.11 + 2.7 / Q_m) % where Q_m = mass flow rate / g/min	Reference meter method at temperatures between ambient and 28 °C

END



10333
Accredited to
ISO/IEC 17025:2017

Schedule of Accreditation
issued by
United Kingdom Accreditation Service
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

Calibra Technology Ltd

Issue No: 006 **Issue date:** 19 September 2023

Calibration performed at main address only

Appendix - Calibration and Measurement Capabilities

Introduction

The definitive statement of the accreditation status of a calibration laboratory is the Accreditation Certificate and the associated Schedule of Accreditation. This Schedule of Accreditation is a critical document, as it defines the measurement capabilities, ranges and boundaries of the calibration activities for which the organisation holds accreditation.

Calibration and Measurement Capabilities (CMCs)

The capabilities provided by accredited calibration laboratories are described by the Calibration and Measurement Capability (CMC), which expresses the lowest measurement uncertainty that can be achieved during a calibration. If a particular device under calibration itself contributes significantly to the uncertainty (for example, if it has limited resolution or exhibits significant non-repeatability) then the uncertainty quoted on a calibration certificate will be increased to account for such factors.

The CMC is normally used to describe the uncertainty that appears in an accredited calibration laboratory's schedule of accreditation and is the uncertainty for which the laboratory has been accredited using the procedure that was the subject of assessment. The measurement uncertainty is calculated according to the procedures given in the GUM and is normally stated as an expanded uncertainty at a coverage probability of 95 %, which usually requires the use of a coverage factor of $k = 2$. An accredited laboratory is not permitted to quote an uncertainty that is smaller than the published measurement uncertainty in certificates issued under its accreditation.

Expression of CMCs - symbols and units

It should be noted that the percentage symbol (%) represents the number 0.01. In cases where the measurement uncertainty is stated as a percentage, this is to be interpreted as meaning percentage of the measurand.
Thus, for example, a measurement uncertainty of 1.5 % means $1.5 \times 0.01 \times q$, where q is the quantity value.

The notation $Q[a, b]$ stands for the root-sum-square of the terms between brackets: $Q[a, b] = [a^2 + b^2]^{1/2}$