## **Schedule of Accreditation**

issued by

## **United Kingdom Accreditation Service**

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK



Accredited to ISO/IEC 17025:2005

Essex CM17 0NS

## **VQS Limited Trading as Valcomm**

Issue No: 003 Issue date: 14 December 2018

Unit 3 Holts Court Contact: Mr Paul Humphries

Threshers Bush Tel: +44 (0)1992 441029 / (0)1279 909130
Harlow E-Mail: paul.humphries@valcomm.co.uk

Website: www.valcomm.co.uk

Calibration performed by the Organisations at the locations specified below

#### Locations covered by the organisation and their relevant activities

#### **Laboratory locations:**

Location details		Activity	Location code
Address Unit 3 Holts Court Threshers Bush	Local contact Mr Paul Humphries	Temperature and relative humidity.	Р
Harlow Essex CM17 0NS	Tel: +44 (0)1992 441029 +44 (0)1279 909130		
	Email: paul.humphries@valcomm.co.uk		

### Site activities performed away from the locations listed above:

Location details	Activity	Location code
The customer's site or premises must be suitable for the nature of the particular calibrations undertaken and will be the subject of contract review arrangements between the laboratory and the customer.	Temperature and relative humidity	S

Assessment Manager: MS1 Page 1 of 2



## Accredited to ISO/IEC 17025:2005

## **Schedule of Accreditation** issued by

# United Kingdom Accreditation Service 2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

## **VQS Limited Trading as Valcom**

Issue No: 003 Issue date: 14 December 2018

Calibration performed by the Organisation at the locations specified

#### **DETAIL OF ACCREDITATION**

Measured Quantity Instrument or Gauge	Range	Calibration and Measurement Capability (CMC) Expressed as an Expanded Uncertainty (k = 2)	Remarks	Location Code		
TEMPERATURE						
Calibration of temperature loggers and probes in an air chamber	5 °C to 10 °C 10 °C to 50 °C	0.23 °C 0.16 °C	Including temperature probes built in to humidity instruments.	P&S		
Temperature indicators and recorders, with temperature sensor(s)	-90 °C to -80 °C -80 °C to 0 °C 0 °C to +100 °C 100 °C to +155 °C +155 °C to +200 °C +200 °C to +300 °C	0.10 °C 0.015 °C 0.025 °C 0.040 °C 0.11 °C 0.35 °C		Р		
	0.01 °C	0.010 °C	In triple point of water cell			
	-90 °C to +140 °C +140 °C to +250 °C	0.10 °C 0.40 °C		S		
Temperature controlled fridges, freezers, incubators, ovens and environmental chambers, including associated recorders, indicators and controllers	-80 °C to 140 °C 140 °C to 250 °C	0.18 °C 0.50 °C	Single or mulit-point	S		
HUMIDITY				P&S		
Relative humidity instruments	5 °C to 10 °C 10 %rh to 90 %rh	2.3 %rh				
	10 °C to 40 °C 5 %rh to 95 %rh	1.60 %rh				
	40 °C to 50 °C 5 %rh to 90 %rh	1.90 %rh				
Humidity controlled chambers, including associated recorders, indicators and controllers	5 °C to 50 °C 10 %rh to 90 %rh	3.0 %rh	Single or mulit-point	S		
END						

Assessment Manager: MS1 Page 2 of 2