

Schedule of Accreditation

issued by

United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

 0925 Accredited to ISO/IEC 17025:2017	Fugro Geoservices Limited	
	Issue No: 013 Issue date: 12 February 2020	
	Fugro House Hithercroft Road Wallingford Oxfordshire OX10 9RB	Contact: Dave Thomas Tel: +44 (0)1491 820 429 E-Mail: D1.thomas@fugro.com Website: www.fugro.com
Testing performed by the Organisation at the locations specified below		

Locations covered by the organisation and their relevant activities

Site activities performed away from the locations listed above:

Location details	Activity	Location code
Ground Investigation Sites	Cone penetration testing including UXO detection	B



0925
Accredited to
ISO/IEC 17025:2017

Schedule of Accreditation
issued by
United Kingdom Accreditation Service
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

Fugro Geoservices Limited
Issue No: 013 Issue date: 12 February 2020

Testing performed by the Organisation at the locations specified

DETAIL OF ACCREDITATION

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used	Location Code
SOILS for civil engineering purposes	Penetration resistance using the fixed 60° cone and friction sleeve (static cone penetration test CPT)	BS 1377- 9:1990 and Eurocode 7, Geotechnical Design, Clause 4.3 Continuous measurement using a penetrometer tip with electrical sensors for cone and sleeve resistance and inclination. BS EN ISO 22476-1:2012	B
	Penetration resistance using the fixed 60° cone and friction sleeve (static cone penetration test CPT)	BS 1377- 9:1990 and Eurocode 7, Geotechnical Design, Clause 4.3, Continuous measurement using a penetrometer tip with electrical sensors for cone and sleeve resistance, inclination and piezometric pressure. BS EN ISO 22476-1:2012	B
	UXO detection for clearance of site investigations and piling using a tri-axial magnetometer	Cone Penetration Testing Procedures Manual.Continuous measurement using a magnetometer housed in a penetrometer with electrical sensors for cone and sleeve resistance, inclination and piezometric pressure.	B
END			