


Schedule of Accreditation

issued by

United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

 <p>UKAS TESTING</p> <p>2459</p> <p>Accredited to ISO/IEC 17025:2017</p>	<h3>Visteon Engineering Services Limited</h3> <p>Issue No: 019 Issue date: 21 December 2021</p>	
	<p>Visteon Engineering Services 31 Springfield Lyons Approach Chelmsford CM2 5LB</p>	<p>Contact: Claire Lewis Tel: +44 (0)1245 395080 Fax: +44 (0)1245 395632 E-Mail: clewis22@visteon.com Website: www.visteon.com</p>
<p>Testing performed at the above address only</p>		

DETAIL OF ACCREDITATION

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
<p>Motor Vehicle's Electronics including: Multi Media, Drive Information and Body Safety, Climate Control, Lighting, Energy Transformation Systems</p>	<p>1 EMC TESTING</p>	
	<p>1.1 Conducted Emissions 150 kHz to 108 MHz</p>	<p>CISPR 25:1995</p>
	<p>1.2 Radiated Electric Field Emissions 150 kHz to 2.5 GHz</p>	<p>CISPR 25:1995 CISPR 25:2002</p>
	<p>1.3 Radiated Electromagnetic Field Immunity: Absorber Lined Chamber 400 MHz to 3.1 GHz up to 300 V/m</p>	<p>ISO 11452-2:2004 ISO 11452-2:1995 ISO 11452-9:2012</p>
	<p>1.4 Conducted Immunity: Transients Load Dump</p>	<p>ISO 7637-0:1990 ISO 7637-1:1990 ISO 7637-2:1990 Pulses 1, 2, 3a, 3b and 5 ISO 7637-3: 2007</p>
<p>1.5 Conducted Immunity BCI, 1 MHz to 400 MHz</p>	<p>ISO 11452-4:2001 ISO 11452-4:2005</p>	



2459
Accredited to
ISO/IEC 17025:2017

Schedule of Accreditation
issued by
United Kingdom Accreditation Service
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

Visteon Engineering Services Limited
Issue No: 019 Issue date: 21 December 2021

Testing performed at main address only

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
As listed on Page 1	1 EMC TESTING (cont'd) 1.6 Electrostatic Discharge Immunity: C = 150 pF, R = 2k Ω , up to \pm 15 kV C = 330 pF, R = 2k Ω , up to \pm 15 kV	ISO 10605:2001
END		