

Schedule of Accreditation

issued by

United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK



4413

Accredited to
ISO/IEC 17025:2005

MS Testing

– a trading division of Mariner Systems (UK) Ltd

Issue No: 017 Issue date: 13 January 2017

5 Maple Way
Aycliffe Industrial Park
Newton Aycliffe
Co Durham
DL5 6BF

Contact: Mr S Thompson
Tel: +44 (0)1325 321366
Fax: +44 (0)1325 319369
E-Mail: info@mstesting.co.uk
Website: www.mstesting.co.uk

Testing performed at the above address only

DETAIL OF ACCREDITATION

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
<p>Electrical installations in ships - Control and instrumentation</p> <p>Maritime navigation and Radio communication equipment and systems</p>	<p>ENVIRONMENTAL TESTS (non-explosive items)</p> <p>CLIMATIC</p> <p>HIGH TEMPERATURE - Constant/Cyclic</p> <p>Max temp: + 70 °C Max chamber size: 1.6 m x 1.9 m x 1.6 m</p> <p>Max temp: + 100 °C Max chamber size: 0.8 m x 0.8 m x 0.8 m</p> <p>Max temp: + 180 °C Max chamber size: 1.2 m x 1.0 m x 1.2 m</p> <p>LOW TEMPERATURE - Constant/Cyclic</p> <p>Min temp: - 25 °C Max chamber size: 1.6 m x 1.9 m x 1.6 m</p> <p>Min temp: - 40 °C Max chamber size: 0.8 m x 0.8 m x 0.8 m</p> <p>Min temp: - 60 °C Max chamber size: 1.2 m x 1.0 m x 1.2 m</p>	<p>BS EN 60068-2-2:2007 IEC 60068-2-2:2007 BS EN 60945, section 8.2.2.2</p> <p>BS EN 60068-2-1:2007 IEC 60068-2-1:2007 BS EN 60945, section 8.4.2.3</p>



Error! Unknown document property name.

Accredited to
ISO/IEC 17025:2005

Schedule of Accreditation
issued by
United Kingdom Accreditation Service
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

MS Testing
– a trading division of Mariner Systems (UK) Ltd
Issue No: 017 Issue date: 13 January 2017

Testing performed at main address only

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
<p>As listed on Page 1</p>	<p>ENVIRONMENTAL TESTS (cont'd)</p> <p>CLIMATIC (cont'd) HIGH HUMIDITY - Constant/Cyclic</p> <p>Humidity range: 10 % rh to 98 % rh (at temps > + 10 °C) Max temperature: + 55 °C Max chamber size: 1.6 m x 1.9 m x 1.6 m</p> <p>SALT MIST Temp range: ambient to + 55 °C</p> <p>INGRESS PROTECTION Protected against solid objects greater than 50 mm dia</p> <p>Protected against solid objects greater than 12.5 mm dia Protected against solid objects greater than 2.5 mm dia Protected against solid objects greater than 1.0 mm dia Dust Protected Dust Tight Protected against splashing water Protected against water jets Protected against powerful water jets Protected against the effects of immersion</p> <p>DYNAMIC</p> <p>VIBRATION - Sinusoidal (ambient temperature) Freq range: 2 to 3000 Hz Max pk/pk displacement: ± 25 mm</p>	<p>IEC 60068-2-30:2005 IEC 60068-2-78:2001 BS EN 60068-2-30:2005 Test Db BS EN 60068-2-78:2002 BS EN 60945, section 8.3</p> <p>IEC 68-2-52:Kb EN 60068-2-52:Kb:1996 BS EN 60945:2002, CI 8.12 Lloyds Spec No 1:2002, CI 16</p> <p>BS EN 60529;1992 Amd 1 & 2 IP1X</p> <p>IP2X</p> <p>IP3X</p> <p>IP4X</p> <p>IP5X IP6X IPX4 IPX5 IPX6 IPX7</p> <p>BS EN 60068-2-6:1996 BS EN 60068-2-6:2008 IEC 60068-2-6:2007 BS EN 60945, section 8.7.2</p>



Error! Unknown document property name.
Accredited to
ISO/IEC 17025:2005

Schedule of Accreditation
 issued by
United Kingdom Accreditation Service
 2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

MS Testing
– a trading division of Mariner Systems (UK) Ltd
Issue No: 017 Issue date: 13 January 2017

Testing performed at main address only

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
As listed on Page 1	DYNAMIC (cont'd)	
	VIBRATION – Random (ambient temperature) Freq range: 2 to 3000 Hz Max pk/pk displacement: ± 25 mm	BS EN 60068-2-64:2008 IEC 60068-2-64:2008
	SHOCK - Half sine (ambient temperature) Max severity: 15 gn Pulse width: 11 ms	BS EN 60068-2-27:1993 BS EN 60068-2-27:2009
	STATIC INCLINATION Max angle: 45° Max item size: 3 m x 3 m x 3 m Max mass: 500 kg	IEC 60092-504:2001
	DYNAMIC INCLINATION Max angle: 45° Max item size: 3 m x 3 m x 3 m Max mass: 500 kg	IEC 60092-504:2001
	ACOUSTIC NOISE Sound pressure level at 1 m 30 to 135 dBA	BS EN 60945, section 11.1
	VOLTAGE TESTS	
	High Voltage Tests 1500V ac	IACS Req:1991/issue 5:2006 E 10 IEC 60947-2
	Insulation Breakdown 500 V dc 100 M Ohms	IEC60092-504 prior to and following Damp heat and low temperature tests in IEC 60945:2002 8.3 and 8.4
	Power supply Variation	IEC 60945:2002 10.7.2
Power Supply Failure	IEC 60945:2002 10.8.2	
	EMC TESTS	
Electrostatic Discharge	IEC 60945:2002 10.9.2 IEC 61000-4-2:2001 IEC 61000-4-2:2008 EN 61000-4-2:2009	
	8 kV Air Discharge	
	6 kV Contact Discharge	



Error! Unknown document property name.

Accredited to
ISO/IEC 17025:2005

Schedule of Accreditation
issued by
United Kingdom Accreditation Service
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

MS Testing
– a trading division of Mariner Systems (UK) Ltd
Issue No: 017 Issue date: 13 January 2017

Testing performed at main address only

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
As listed on Page 1	EMC TESTS (cont'd)	
	Electrical Fast Transient Bursts 2 kV	IEC 60945:2002 10.5.2 IEC 61000-4-4:2004 EN 61000-4-4:2004 EN 61000-4-4:2004 + A1:2010 EN 61000-4-4: 2012
	Surge 2 kV	IEC 60945:2002 10.6.2 IEC 61000-4-5:2005 EN 61000-4-5:2006
	Compass Safe Distance	IEC 60945:2002 11.2
	Radiated Immunity 80 to 2000 MHz, 10 V/m 2000 to 2700 MHz, 3 V/m	IEC 60945:2002 10.4.2 EN 61000-4-3:2006 + A1:2008 EN 61000-4-3: 2006 + A1: 2008 + A2: 2010
Conducted Emissions 9 kHz to 30 MHz	IEC 60945:2002 9.2.2 EN 55016-2-1:2009 EN 55016-2-1: 2009 + A2: 2013 EN 55016-2-1: 2014 EN 55022: 2006+ A1:2007 (excluding telecommunication ports) EN 55022: 2010 EN 55032: 2015 Excluding antenna port EN 55014-1:2006 EN 55014-1: 2006 + A1:2009 EN 55011:2009 +A1:2010 (excluding Group 2 apparatus)	



Error! Unknown document property name.
Accredited to
ISO/IEC 17025:2005

Schedule of Accreditation
issued by
United Kingdom Accreditation Service
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

MS Testing
– a trading division of **Mariner Systems (UK) Ltd**
Issue No: 017 Issue date: 13 January 2017

Testing performed at main address only

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
As listed on Page 1	EMC TESTS (cont'd)	
	Radiated Emissions 150 kHz to 3000 MHz	IEC 60945:2002 9.3.2 EN 55016-2-3:2006 AN 55016-2-3: 2006 + A1: 2007 + A2: 2014 EN 55022:2006 + A1:2007 EN 55022: 2010 EN 55032: 2015 EN 55014-1:2006 EN 55014-1: 2006 + A1:2009 EN 55011:2009 + A1:2010 (excluding Group 2 apparatus) EN 55011:2016 (excluding Group 2 apparatus)
	Discontinuous Emissions (Clicks): 10 kHz to 30 MHz	EN 55014-1:2006 + A1:2009
	Conducted Current Harmonics (Emissions) Measurements up to 40 th Harmonic Equipment Input Current ≤ 16A per phase	EN 61000-3-2:2006 +A2:2009 EN 61000-3-2:2014
	Conducted AC Mains Flicker (Emissions)	EN 61000-3-3:2008 EN 61000-3-3: 2013
	Voltage Dips and Interruptions	EN 61000-4-11:2004
	Power Absorbing Emissions Measurements (Power Clamp) 30 to 300 MHz	EN 55014-1:2006 EN 55014-1: 2006 + A1: 2009 EN 55016-2-2:2004 +A1:2005, + A2:2005
	Conducted Low Frequency Immunity 50 Hz - 10 kHz	IACS E10: 2006 IACS E10: 2014



Error! Unknown document property name.
Accredited to
ISO/IEC 17025:2005

Schedule of Accreditation
 issued by
United Kingdom Accreditation Service
 2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

MS Testing
– a trading division of Mariner Systems (UK) Ltd
Issue No: 017 Issue date: 13 January 2017

Testing performed at main address only

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
As listed on Page 1	EMC TESTS (cont'd) Conducted Radio Frequency Immunity 150 kHz to 230 MHz RF Voltage up to 10 V rms	EN 61000-4-6:2009 EN 61000-4-6: 2014
	Power Frequency Magnetic Fields (Immunity) Frequency: DC to 1 kHz Field Strength: Up to 30 A/m	EN 61000-4-8:1993 + A1:2001 EN 61000-4-8: 2010
	Power-Frequency Magnetic Fields (Immunity) (Pulsed) Field Strength: Up to 1000 A/m Product Standards The EMC standards listed are accredited to the extent that they call up the basic standards as accredited within this schedule.	EN 61000-4-9:1993 +A1:2001 EN 50130-4:1994 + A1:1998, A2:2003 EN 50270:2006 EN 55014-2:1997 + A2:2008 EN 55024:1998 + A1:2001 & A2:2003 EN 55024:2010 + A1:2015 EN 61000-6-1:2007 EN 61000-6-2:2005 EN 61000-6-3:2007 EN 61000-6-3:2007 + A1:2011 EN 61000-6-4:2007 EN 61000-6-4:2007 + A1:2011 EN 61326-1:2006 EN 61326-1:2013 EN 61326-2-6:2013 EN 50121-4:2006
END		