

Schedule of Accreditation

issued by

United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK



7670

Accredited to
ISO/IEC 17025:2005

Axis Test Laboratories Ltd

Issue No: 007 Issue date: 21 July 2017

Unit 11A
Oakway Court
Meadowfield Industrial Estate
Durham
DH7 8XD

Contact: Mr A. Dixon
Tel: +44 (0)191 3784653
E-Mail: info@axistestlaboratories.co.uk
Website: www.axistestlaboratories.co.uk

Testing performed at the above address only

DETAIL OF ACCREDITATION

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
Maritime navigation and radio-communication equipment and systems	<p>ENVIRONMENTAL TESTS (Non-explosive items)</p> <p>CLIMATIC - Single Parameters</p> <p>DRY HEAT Constant/Cyclic Max temperature: +180 °C</p> <p>Max chamber size: 0.9 m x 0.9 m x 0.9 m</p> <p>COLD TEST Constant/Cyclic Min temperature: -70 °C</p> <p>Max chamber size: 0.9 m x 0.9 m x 0.9 m</p> <p>HUMIDITY Constant/Cyclic Humidity range: 10% rh to 98% rh at 55 °C</p> <p>Max chamber size: 0.9 m x 0.9 m x 0.9 m</p> <p>CORROSION, SALT (salt spray) cyclic</p>	<p>BS EN 60068-2-2:2007 IEC 60068-2-2:2007 BS EN 60945:2002 & IEC 60945:2002, section 8.2.2.2 MIL-STD 810G Method 520 Para 235-236*</p> <p>BS EN 60068-2-1:2007 IEC 60068-2-1:2007 BS EN 60945:2002& IEC 60945:2002 , section 8.4.2.3 MIL-STD 810G Method 520 Para 235-236*</p> <p>IEC 60068-2-30:2005 BS EN 60068-2-30:2005 Test Db BS EN 60945:2002& IEC 60945:2002 , section 8.3 MIL-STD 810G Method 520 Para 235-236*</p> <p>*Excluding simultaneous vibration testing</p> <p>BS EN 60068-2-52:1996 BS EN 60945:2002& IEC 60945:2002 , section 8.12 MIL-STD 810G Method 509.5</p>



7670

Accredited to
ISO/IEC 17025:2005

Schedule of Accreditation

issued by

United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

Axis Test Laboratories Ltd

Issue No: 007 Issue date: 21 July 2017

Testing performed at main address only

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
	<p>DYNAMIC - Single Parameters</p> <p>VIBRATION - Sinusoidal (ambient temperature) Freq range: 2 to 3000 Hz Max pk/pk displacement:: +/-25 mm Max load (static): 1000 kg</p>	<p>BS EN 60068-2-6:1996 BS EN 60068-2-6:2008 IEC 60068-2-6:2007 BS EN 60945:2002& IEC 60945:2002 , section 8.7</p>
Maritime navigation and radio-communication equipment and systems (cont'd)	<p>ENVIRONMENTAL TESTS (Non-explosive items) (cont'd)</p> <p>DYNAMIC - Single Parameters (contd)</p> <p>VIBRATION - Random (ambient temperature) Freq range: 2 to 3000 Hz Max pk/pk displacement:: +/-25 mm Max load (static): 1000 kg</p> <p>VIBRATION – Sine on Random Random on random (ambient temperature) Freq range: 2 to 3000 Hz Max pk/pk displacement:: +/-25 mm Max load (static): 1000 kg</p> <p>SHOCK - Half sine (ambient temperature) Max severity: 15 gn Pulse width: 11 ms Max load (static): 1000 kg</p> <p>Insulation Resistance</p>	<p>BS EN 60068-2-64:2008 BS EN 60068-2-64:1995 EN ISO 13355:2003</p> <p>MIL_STD_810G Method 514.6 Excludes 4.1.3</p> <p>BS EN 60068-2-27:1993 BS EN 60068-2-27:2009</p> <p>IEC60092-504:2001</p>



7670

Accredited to
ISO/IEC 17025:2005

Schedule of Accreditation

issued by

United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

Axis Test Laboratories Ltd

Issue No: 007 Issue date: 21 July 2017

Testing performed at main address only

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
Complete, filled transport packages	PERFORMANCE TESTS Method for determination of resistance to vertical impact by dropping (Box Drop) Maximum height: 1.5m Maximum weight: 70Kg	BS EN 22248:1993 ISO 2248:1985
END		